# AUTOMATIC TOILET

# FARAH SHARIDAH BINTI AB.GAFOR

This Report Is Submitted In Partial Fulfillment Of Requirement For The Bachelor

Degree of Electronic Engineering (Industrial Electronic)

Fakulti Kejuruteraan Elektronik dan Kejuruteraan Komputer Universiti Teknikal Malaysia Melaka

June 2013





# **UNIVERSTI TEKNIKAL MALAYSIA MELAKA** FAKULTI KEJURUTERAAN ELEKTRONIK DAN KEJURUTERAAN KOMPUTER

# BORANG PENGESAHAN STATUS LAPORAN PROJEK SARJANA MUDA II

*AIND		
Tajuk Projek :	AUI	TOMATIC TOILET
Sesi Pengajian :	2012	2 / 2013
mengaku membenark syarat kegunaan seper 1. Laporan adalah h	an Laporan Proj rti berikut: akmilik Univers	ARIDAH BINTI AB:GAFOR (HURUF BESAR) jek Sarjana Muda ini disimpan di Perpustakaan dengan syarat- siti Teknikal Malaysia Melaka.
•		at salinan untuk tujuan pengajian sahaja.
<ol><li>Perpustakaan dib</li></ol>	enarkan membu	nat salinan laporan ini sebagai bahan pertukaran antara institusi
pengajian tinggi.		
4. Sila tandakan (	√):	
SULIT TERH		*(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972)  **(Mengandungi maklumat terhad yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan)
		Disahkan oleh:
,	FANGAN PENULIS  p: B.282 JALAN I  FELDA ULU B  86007 KLUAN  JOHOR	KEMBOJA, BELITONG,
Tarikh:	····23·MEI 2013	Tarikh:23-MEI 2013

"I hereby declare that this report is the result of my own work except for quotes as cited in the references."

> Signature .

Author : Farah Sharidah Binti Ab.Gafor

: May 23, 2013 Date

"I hereby declare that I have read this report and in my opinion this report is sufficient in terms of the scope and quality for the award of Bachelor Degree of Electronic Engineering (Industrial Electronic)."

Signature

Supervisor's Name : Engr. Siti Fatimah Binti Sulaiman

Date : May 23, 2013 Special dedicated to my beloved parents Mr. Ab.Gafor bin Sultan and Mrs. Fazidah binti Dirin, my lovely siblings, my kindly supervisor Engr. Siti Fatimah binti Sulaiman, and special greeting to the dear friends.

### **ACKNOWLEDGEMENT**

First of all, it's grateful to our God Allah S.W.T because with His permission I am able to complete "Project Sarjana Muda" (PSM) as a requirement for graduation in Bachelor Degree of Electronic Engineering (Industrial Electronic) from Universiti Teknikal Malaysia Melaka (UTeM). Also, I would like to appreciate Engr. Siti Fatimah binti Sulaiman, my project supervisor that is always helping getting through hard times to complete this project. With her willingly guidance and words of advice, I manage to complete this project within a time.

In addition, I would like to express my gratitude to the panel members who gave me some advice in order to improve the performance of the project. Moreover to all laboratory technician and lab assistance in FKEKK UTeM, that were involved in this project and also guiding me during the fabrication process. Furthermore, to my fellow friends especially my course mates that had been with me since 2009, thanks for your kindness and support.

Last but not least, to my beloved family who always give me a support during my studies, thanks all for your love, pray, and attentions.

### **ABSTRACT**

Toilet hygiene is one factor for the user to use the toilet. Most public toilets in Malaysia have poor hygiene though various campaigns have been carried out to improve cleanliness. But, do these things happen due care casualness of the parties should be, or as a result of the users own attitude? Therefore automatic toilet system has been created aimed to teach people to keep public toilets clean. The system is also loaded with light and fan which is on and off when the toilet is use and not in use. This automated system saves electricity. Before using the automatic toilet users must make a payment of twenty cents, to enable the doors to be opened because the toilet door is always locked. It is controlled by using solenoid actuator. Solenoid works as the same ways as normal Direct Current (DC) motor, in order to trigger in both directions two relays are used. The system at once reduces the labor. Upon completion using automatic toilet, users have to press flush to allow the door opened. The system is able to educate Malaysians especially to ensure cleanliness of the public toilet. Music is also included in the automatic toilet system which is designed to give comfort to the toilet user. Automatic toilet system is controlled by Programmable Interface Controller (PIC16F877A) and is program using C program.

### **ABSTRAK**

Kebersihan sesebuah tandas itu merupakan salah satu faktor bagi pengguna untuk menggunakan tandas tersebut. Kebanyakan tandas awam di Malaysia mempunyai tahap kebersihan yang rendah walaupun pelbagai kempen telah dijalankan untuk meningkatkan kebersihan tandas. Tetapi, adakah perkara tersebut berlaku disebabkan penjagaan yang sambil lewa daripada pihak yang sepatutnya ataupun hasil daripada sikap pengguna itu sendiri? Oleh sebab itu tandas automatik ini telah dicipta bertujuan untuk mengajar orang ramai supaya menjaga kebersihan tandas awam. Sistem ini juga dimuatkan dengan kawalan lampu dan kipas yang menyala apabila tandas digunakan dan terpadam apabila tandas tidak digunakan secara automatik. Sistem automatik ini dapat menjimatkan penggunaan tenaga elektrik. Sebelum meggunakan tandas, pengguna haruslah membuat pembayaran sebanyak dua puluh sen bagi membolehkan pintu dibuka, kerana pintu tandas akan sentiasa berkunci jika tidak digunakan. Pintu ini dikawal oleh penggerak solenoid. Solenoid berfungsi sama seperti motor Arus Terus (AT) biasa. Untuk membolehkan solenoid bertindak dalam dua arah, dua geganti digunakan. Sistem ini sekaligus dapat mengurangkan tenaga pekerja kerana duit dimasukkan secara automatik. Setelah siap menggunakan tandas, pengguna haruslah menekan pemancur bagi membolehkan pintu dibuka semula. Sistem ini dapat mendidik rakyat Malaysia terutamanya untuk menjaga kebersihan tandas kerana kebersihan tandas tanggungjawab bersama. Muzik juga dimuatkan dalam sistem tandas automatik ini bertujuan memberi keselesaan kepada pengguna tandas. Sistem tandas automatik ini dikawal oleh Pengawal Antaramuka Perisian (PIC16F877A) dan diprogram menggunakan program C.

# **TABLE OF CONTENTS**

CHAPTER	TITLE	PAGE
	PROJECT TITLE	i
	CONFIRMATION OF STATUS REPORT	ii
	DECLARATION	iii
	SUPERVISOR DECLARATION	iv
	DEDICATION	v
	ACKNOWLEGMENT	vi
	ABSTRACT	vii
	ABSTRAK	viii
	TABLE OF CONTENTS	ix
	LIST OF FIGURES	xiii
	LIST OF TABLES	xvi
	LIST OF ABREVIATIONS	xvii
	LIST OF APPENDICES	xviii
I	INTRODUCTION	
	1.1 OVERVIEW	1
	1.2 OBJECTIVE	3
	1.3 PROBLEM STATEMENTS	4
	1.4 SCOPE OF PROJECT	4
	1.5 REPORT STRUCTURE	5

# II LITERATURE REVIEW

	2.1	OVERV	VIEW	6
	2.2	AUTO	MATIC TOILET SYSTEM	8
	2.3	SYSTE	M DESIGN	10
		2.3.1	System's input	11
		2.3.2	System's output	11
	2.4	POWE	R DOOR LOCK	13
		2.4.1	Auto flush	15
		2.4.2	Automatic room light	16
	2.5	PROGE	RAMMABLE INTEGRATED CIRCUIT	18
		(PIC)		
	2.6	PIN DI	AGRAMS of PIC16F877A	18
III	MET	гнорог	LOGY	
	3.1	OVERV	VIEW	19
	3.2	PROJE	CT FLOW CHART	19
		3.2.1	Overall of methodology	21
		3.2.2	Hardware development	22
		3.2.3	Software development	24
		3.2.4	Combining software and hardware	25
	3.3	CHOSE	EN COMPONENTS	26
		3.3.1	Resistor	26
		3.3.2	Light Emitting Diode (LED)	28
		3.3.3	PIC16F877A	28
		3.3.4	Button	29
		3.3.5	LM7805	30
		3.3.6	Relay	30
		3.3.7	Diode	31
		3.3.8	Capacitor	32
		3.3.9	Push button	33

		3.3.10	Solenoid	34
		3.3.11	ULN2803	34
		3.3.12	Aquarium pump	35
	3.4	PCB FA	ABRICATION	36
		3.4.1	Steps of PCB fabrication	36
		3.4.2	Drilling	38
		3.4.3	Soldering	39
		3.4.4	Solder	39
		3.4.5	Flux	39
		3.4.6	Soldering iron	40
		3.4.7	Characteristics of a poor solder joints	40
	3.5	CIRCU	IT DIAGRAM IN PCB	42
	3.6	SOFTV	VARE	44
	3.7	DECLA	ARATION PINS OF PIC FOR PROJECT	45
IV	PRO	JECT DI	ESIGN	
IV	<b>PRO</b> 4.1	JECT DE		46
IV		OVER	VIEW	46 47
IV	4.1	OVER'S	VIEW	
IV	4.1 4.2	OVERVINPUT	VIEW PART	47
IV	4.1 4.2 4.3	OVERVINPUT OUTPU	VIEW PART JT PART	47 48
IV	4.1 4.2 4.3 4.4	OVERY INPUT OUTPU PROTO PROJE	VIEW PART JT PART OTYPE DESIGN	47 48 49
IV	4.1 4.2 4.3 4.4 4.5	OVERY INPUT OUTPU PROTO PROJE	VIEW PART JT PART OTYPE DESIGN CT SCHEDULE	47 48 49 52
IV V	4.1 4.2 4.3 4.4 4.5 4.6	OVERY INPUT OUTPU PROTO PROJE COST	VIEW PART JT PART OTYPE DESIGN CT SCHEDULE	47 48 49 52
	4.1 4.2 4.3 4.4 4.5 4.6	OVERY INPUT OUTPU PROTO PROJE COST	VIEW PART JT PART OTYPE DESIGN CT SCHEDULE OF PROJECT	47 48 49 52
	4.1 4.2 4.3 4.4 4.5 4.6	OVERY INPUT OUTPU PROTO PROJE COST	PART UT PART OTYPE DESIGN CT SCHEDULE OF PROJECT  D ANALYSIS	47 48 49 52 53
	4.1 4.2 4.3 4.4 4.5 4.6	OVERY INPUT OUTPU PROTO PROJE COST OULT ANI	PART UT PART OTYPE DESIGN CT SCHEDULE OF PROJECT  D ANALYSIS	47 48 49 52 53
	4.1 4.2 4.3 4.4 4.5 4.6 <b>RES</b>	OVERY INPUT OUTPU PROTO PROJE COST OULT ANI OVERY	VIEW PART JT PART OTYPE DESIGN CT SCHEDULE OF PROJECT  D ANALYSIS VIEW CT OF PROJECT	47 48 49 52 53 54 55

#### $\mathbf{V}$ CONCLUSION AND RECOMMENDATION

CONCLUSION	61
RECOMMENDATION	62
REFERENCES	63
APPENDIX	64

# LIST OF FIGURES

FIGURE	TITLE	PAGE
2.1	System structure drawing	10
2.2	Motor or door lock wiring (lock)	12
2.3	Motor or door lock wiring (open)	12
2.4	Door lock actuator	13
2.5	Moving part	13
2.6	Hole for actuator	14
2.7	Positioning clamp	14
2.8	Two straps	14
2.9	HLCM wiring	17
2.10	Pin diagram of PIC16F877A	18
3.1	Project flow chart	20
3.2	Overall of methodology	21
3.3	Hardware development	22
3.4	Software development	24
3.5	Combining software and hardware flow chart	25
3.6	Resistor	26
3.7	Light Emitting Diode (LED)	28
3.8	PIC16F877A	29
3.9	Reset button	29
3.10	LM7805 (voltage regulator)	30
3.11	Relay	31
3.12	Diode	31
3.13	Capacitor	32

3.14	Push button	33
3.15	Door lock dc motor	34
3.16	ULN2803	35
3.17	Aquarium pump	35
3.18	Process photoresist	36
3.19	Light exposure process	37
3.20	Etching process	38
3.21	Drilling process	38
3.22	Soldering process	39
3.23	PCB layout for input circuit (top layer)	42
3.24	PCB layout for output circuit (top layer)	42
3.25	PCB layout for input circuit (bottom layer)	43
3.26	PCB layout for output circuit (bottom layer)	43
4.1	Block diagram of design project	46
4.2	Input circuit	47
4.3	Output circuit	48
4.4	Flow chart making the prototype	49
4.5	Prototype in process	50
4.6	Attached the component	50
4.7	Prototype automatic toilet	51
4.8	Front view of automatic toilet	51
4.9	Gantt chart of project planning	52
5.1	Money slot	55
5.2	PIC16F877A	55
5.3	Lamp, fan, and buzzer	55
5.4	Light Emitting Diode (LED) turn ON	56
5.5	Solenoid backward	56
5.6	Solenoid forward	56
5.7	Flush	57
5.8	Toilet tank	57
5.9	Water level sensor	57
5.10	Motor 2	58
5.11	Door	58

# LIST OF TABLES

TABLE	TITLE	PAGE
2.1	Power door lock system	13
3.1	Calculating the value of resistors	27
3.2	Capacitor value codes	32
3.3	Declaration pins input and output at PIC	45
4.1	Cost of project	53
5.1	Result	55

# LIST OF ABREVIATIONS

- Programmable Integrated Circuit

PIC

- Transistor-Transistor Logic

TTL

- Light Emitting Diode

LED

- Peripheral Interface Controller

PC

- Ultraviolet

UV

Programmable Logic Controller

PLC

Random Access Memory

RAM

Electrically Erasable Programmable Read Only Memory

**EEPROM** 

- Home Light Control Module

HLCM

- Personal Computer

PC

Direct Current

DC

- Radio Frequency

RF

- Arus Terus

AT

# LIST OF APPENDICES

NO.	TITLE	PAGE
A	Code program for automatic toilet	63

### **CHAPTER I**

### INTRODUCTION

### 1.1 Overview

A toilet is a sanitation fixture used primarily for the disposal of human excrement and urine, often found in a small room referred to as a toilet, bathroom, and lavatory. A public toilet also called a bathroom, restroom, latrine, comfort room, powder room, toilet room, washroom, water closet, public lavatory, and convenience is a room or small building containing one or more toilets and possibly also urinals which is available for use by the general public, or in a broader meaning of public, by customers of other services. Public toilets are commonly separated by gender into male and female facilities, although some can be unisex, particularly the smaller or single occupancy types. Increasingly, public toilets incorporate accessible toilets and features to cater for people with disabilities. Public toilets may be unattended or be staffed by a janitor possibly with a separate room, or attendant, provided by the local authority or the owner of the larger building. In many cultures, it is customary to tip the attendant, while other public toilets may charge a small fee for entrance, sometimes through use of a coin operated turnstile. Some venues such as nightclubs may feature a grooming service provided by an attendant in the toilet. They are typically found in railway stations, schools, bars, restaurants, nightclubs or filling stations as well as on longer distance public transport vehicles. Portable toilets are often provided at festivals and at temporary events for public use.

Public toilets are valuable assets that should be kept comfortably used by the public. Bad attitude some users and is not responsible polluter is the cause of the foul smelling toilet. Public toilets should be kept clean and comfortable to use. Toilet hygiene is important to prevent the spread of germs and bacteria. Cleanliness also symbolizes the individuality of the people of Malaysia especially for the tourists who come to Malaysia.

On the basis of the responsibility the project of an 'Automatic Toilet' was created. Automatic toilet project was created to educate the public to keep public toilets clean. The toilet is controlled by an automatic system designed to save electricity. Automatic toilet is also equipped with an automatic payment system using the slot money before entering the toilet, aimed at reducing the workforce responsible for working out the toilet to charge before using the toilet. Before using the toilet should ensure LED is green, indicating no user in the toilet. Cheap charge that is applies to use the toilet only twenty cents. Twenty cent coin to be inserted into the slot money to allow the door opened. After entering the toilet, red LED lights is on, the door will be locked and will not be open as long as the flush is not pressed. When the user goes into the toilet, light, fan, and music will be on automatically. When the users have finished using the toilet, press the flush to allow the door opened. When users are out, the light, fan and music will be goes off automatically. After a few seconds door will be locked and the green LED lights up means it can be used toilet. Water in the tank is controlled by a water level sensor which when pressed flush, motor 1 will on to pump water into the toilet tank. When the water level sensor detects water in the tank 1 is empty, motor 2 will on to fill the tank 1. When the tank 1 is full motor 2 will stop pumping water. All inputs and outputs of the system are automatically controlled by PIC16F877A and C program.

### 1.2 Objectives

Ministry of Housing and Local Government said, 'Although it has many campaigns keeping public toilets clean but the toilet still very bad performance from time to time'. Therefore, this project is designed to teach and educate the public to keep public toilets clean, which is users must press the flush after finished using the toilet to enable the doors to be opened because the toilet door is locked. It is controlled by using solenoid, solenoid works as the same ways as normal DC motor, in order to trigger in both directions two relays are used. In addition the project is loaded with features light, fan, and music that comes on when there are user and off when no user. This is intended to save energy consumption. Light and fan do not need to be constantly running, even no user in the toilet. Apart from that, the main input to the system is the use of an automatic toilet money slot where the user must make a payment of twenty cents to use the toilet. When money slots accept coins, money slot will send pulse to PIC16F877A. PIC16F877A will receive pulse and carry out its functions. PIC16F877A is used to run all the automated system's toilet. C program is used to compile all this toilet automated system. Money slot system is designed to reduce labor.

### Objectives of the project are:

- 1. To maintain the cleanliness of public toilets.
- 2. To conserve electricity, because the system will work only after the user goes into the toilet.
- 3. To reduce labor, because the money is automatically inserted.

### 1.3 Problem Statements

Nowadays, has many radio stations aired in Malaysia, to get a general view about the level cleanliness of public toilets in Malaysia. On average than they say public toilets in Malaysia are not satisfactory, and there is also a flattering public toilets in foreign countries so clean compared to Malaysia. Undoubtedly, there are public toilets are so dirty, no appetite to see what more to get into it. This often happens in restaurants, shopping malls and even toilets at highway stops. Automatic toilet project is designed to handle the problem of dirty public toilet.

### 1.4 Scope of Projects

The scope of this project is to investigate and research some information related to the automatic toilet. The project is divided into two parts which are hardware and software, software which is C program and hardware which is PIC16F877A that control all functions of the automatic toilet, and hardware also including the prototype. Hardware design of the materials and find resources on the right track with the project. Paramount concerns in hardware design are the ability of the circuit, price and size. In addition, it should ensure that the project will be fully functional when all the necessary circuits combined together in the design. Although the software design is focused on finding and reviewing software for the project, but the software can also be combined with the hardware. Software used for this project should be suitable, simple program design, and easy to understand functions.

# 1.5 Report Structure

This thesis is organized in six chapters accordingly. The first part of this thesis discusses the concept of automatic toilets, working methods, and objectives.

The second part of the literature review described automatic toilets and public toilets study background.

The third part of the project methodology which covered the design and development of automatic toilet system.

The fourth part of Chapter IV of the protected design the project and how the project functions in accordance with the methodology.

The fifth part of Chapter V consists of results and automatic toilet system application also includes analysis and software projects.

Finally, the last part is the concluding part of the overall development of the project and how to fix it properly.

### **CHAPTER II**

### LITERATURE REVIEW

### 2.1 Overview

World Toilet Day Celebrations at the national level is part of the Clean Toilet Campaign activities carried out by Ministry of Housing and Local Government through the Department of the local. This response is intended to remind people about the practice good care and clean toilets and thereby improving image cleanliness of public toilets in the country.

On the initiative of the World Toilet Organization or the World Toilet Organization, World Toilet Day was started in 2001. This year was a celebration for the 10th time. World Toilet Day Celebration theme globally 2011 was Toilet Civilizations Health Tourism, Quality of Life.

In addition to alerting the world community about the practice of good hygiene toilet, it also seeks to remind the inhabitants of the earth about the sanitation crisis in some of the less developed countries.

Professor Jenna Davis findings from the Faculty of Civil and Environmental Engineering, Stanford University, United States, showed that about 40%, 2.6 Billion the world's population still lacks access to basic toilet facilities.