



Faculty of Mechanical Engineering

**INVESTIGATION ON THERMAL PERFORMANCE OF
PROSPECTIVE GREEN MATERIALS AS BUILDING WALL
INSULATION**

Wong Eu Lik

Bachelor Degree in Mechanical Engineering

2018

**INVESTIGATION ON THERMAL PERFORMANCE OF PROSPECTIVE GREEN
MATERIALS AS BUILDING WALL INSULATION**

WONG EU LIK

B041410296

BMCG

wel1994@hotmail.com

Report

Projek Sarjana Muda

Supervisor: DR. TEE BOON TUAN

Second Examiner: DR. MOHD AFZANIZAM BIN MOHD ROSLI

Faculty of Mechanical Engineering

Universiti Teknikal Malaysia Melaka

2018

DECLARATION

I declare that this thesis entitled “Investigation on Thermal Performance of Prospective Green Materials as Building Wall Insulation” is the result of my own research except as cited in the references. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

Signature :.....
Name :.....
Date :.....

APPROVAL

I hereby declare that I have read this report and in my opinion this report is sufficient in terms of scope and quality as a partial fulfillment of bachelor degree of Mechanical Engineering.

Signature :.....
Supervisor Name :.....
Date :.....

DEDICATION

To my beloved mother and father

ABSTRACT

The building construction industry is recently changing focus in using sustainable and green materials. With the abundance of the resources, it is beneficial to utilize the application and observing its potential as wall insulation materials. This study is hoped to provide some prospect in using green materials as wall insulation. Building insulation is defined as any object in a building, such as roof and wall are used as insulation for any purpose. Thermal insulator in buildings is an important factor to achieve thermal comfort for its occupants. By installing the insulator in a building, it will reduce the unwanted heat loss or gain and can also decrease the energy demands of heating and cooling systems. Besides that, the study tends to set as a benchmark study for further application of green materials in building construction. In this project, green waste materials is chosen to analysis and perform the heat transfer test. Green materials used in this study are coconut fibres, cellulose and sugar cane wastes. The objective of this study is to analysis the behaviour and thermal insulation of the selected green materials. The measurement is conducted by installing the green materials samples in mini house model and infrared camera is used to record the temperature gradient in the mini house model under different conditions. Thermal conductivity of each insulator is calculate to determine the thermal behaviour of these insulators.

ABSTRAK

Industri pembinaan bangunan baru-baru ini mengubah tumpuan dalam menggunakan bahan-bahan mampan dan hijau. Dengan adanya sumber yang banyak, aplikasi dan potensinya sebagai bahan penebat dinding telah dipehertikan. Kajian ini diharapkan dapat menyediakan beberapa prospek dalam menggunakan bahan hijau sebagai penebat dinding. Penebat bangunan ditakrifkan sebagai sebarang objek di dalam bangunan, seperti penebat di bumbung dan dinding untuk mencapai tujuan tertentu. Penebat haba dalam bangunan merupakan faktor penting untuk mencapai keselesaan terma bagi penghuninya. Dengan memasang penebat di bangunan, ia akan mengurangkan kehilangan atau kenaikan haba yang tidak diingini dan juga dapat mengurangkan permintaan terhadap tenaga pemanasan dan penyejukan. Di samping itu, kajian ini cenderung kepada penggunaan bahan hijau dalam pembinaan bangunan. Dalam projek ini, bahan buangan hijau dipilih untuk dianalisis dan melaksanakan ujian pemindahan haba. Bahan-bahan hijau yang digunakan dalam kajian ini adalah sisa-sisa kelapa, selulosa dan sisa tebu. Objektif kajian ini adalah untuk menganalisis tingkah balas dan penebat haba bahan-bahan hijau terpilih. Pengukuran dilakukan dengan memasang sampel bahan hijau dalam model rumah dan kamera inframerah digunakan untuk merekam kecerunan suhu dalam model rumah dalam keadaan yang berbeza. Kekonduksian haba bagi setiap penebat akan dikira untuk menentukan tahap kelakuan haba penebat tersebut.

ACKNOWLEDGEMENTS

I would like to express my deepest appreciation to all those who have provided me the possibility to complete my Projek Sarjana Muda 1. I would like to give special gratitude to my supervisor, Dr Tee Boon Tuan, who has helped me so much by constantly imparting his knowledge and ideas so that I could successfully complete this project on a high note.

Besides that, I would also like to acknowledge with much appreciation to Dr. Mohd Afzanizam Bin Mohd Rosli and Prof. Dr. Md. Razali Bin Ayob for evaluating my Projek Sarjana Muda 1. All the suggestions and inputs which were given to me during the seminar will be valuable for me to complete my Projek Sarjana Muda 2. Special thanks to Encik Asjufri, the technician from air conditioning system Faculty of Mechanical Engineering, for his continuous guidance and assistance during the lab and analysis works.

Furthermore, I would also like to thank Faculty of Mechanical Engineering (FKM) or Universiti Teknikal Malaysia Melaka (UTeM) for giving me this opportunity to complete this project and allowing me to utilize all the necessary equipment and tools that I needed to use for this study.

Last but not least, many thanks to all my family and friends for their constant support and encouragement throughout this tedious but fruitful period, which without them I would not have been able to complete this report successfully.

TABLE OF CONTENTS

	PAGE
DECLARATION	
APPROVAL	
DEDICATION	
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENT	iii
TABLE OF CONTENT	iv – vi
LIST OF TABLES	vii – viii
LIST OF FIGURES	ix – x
LIST OF APPENDICES	xi
LIST OF SYMBOLS	xii
LIST OF ABBREVIATIONS	xiii
CHAPTER	
1. INTRODUCTION	
1.1 Background of Problem	1
1.2 Problem Statement	3
1.3 Objective	4
1.4 Scope of Research	4
1.5 Project Organization	5
1.6 Important of the Work	6
2. THEORY	
2.1 Thermal Insulator	7
2.2 Heat Conduction in Plane Wall	
2.2.1 Heat Conduction	8
2.2.2 Thermal Conductivity	9
2.2.3 Thermal Resistance	11
2.3 Infrared Photon Analysis	
2.3.1 Thermography	11
2.4 Green Material	13
3. LITERATURE REVIEW	
3.1 Do green roofs cool the air? By Anna, Frans, Mengyu, Michiel and Nick (2017)	15
3.1.1 Methodology	15

3.1.2	Result and Discussion	17
3.1.3	Conclusion	18
3.2	An Experimental Method to Quantitatively Analyse the Effect of Thermal Insulation Thickness on the Summer Performance of a Vertical Green Wall by Olivieri (2017)	18
3.2.1	Methodology	19
3.2.2	Result and Discussion	24
3.2.3	Conclusion	26
3.3	Application of Coconut Fibres as Outer Eco-insulation to Control Solar Heat Radiation on Horizontal Concrete Slab Rooftop by Danny, Wanda and Anik (2015)	27
3.3.1	Methodology	28
3.3.2	Result and Discussion	29
3.3.3	Conclusion	31
3.4	Sugar Cane Bagasse Fibres Reinforces Cement Composite: Thermal Considerations by Cristel, Nady, Fernando, Silvio, Ketty and Marie (2010)	31
3.4.1	Methodology	32
3.4.2	Result and Discussion	32
3.4.3	Conclusion	35
3.5	A Review on the Properties of Cellulose Fibre Insulation by Pablo, Antoine, Virginie and Christine (2016)	35
3.5.1	Methodology	36
3.5.2	Result and Discussion	37
3.5.3	Conclusion	40
4.	METHODOLOGY	
4.1	Green Materials Selection	42
4.2	Green Materials Product Sample Preparation	44
4.2.1	Cellulose Sample Preparation	44
4.2.2	Sugar Cane Waste and Coconut Fibre Sample Preparation	45
4.2.3	Ratio Contain of Green Material and Glue	47
4.3	Experimental Set-up	48
4.4	Physical Measurement using Thermal Imaging Camera	52
4.5	Thermocouple	53
4.6	Heat Transfer Conduction Analysis	54
5.	RESULT	55
5.1	Polystyrene	58
5.2	Fibreglass	61
5.3	Cotton	64
5.4	Wool	67
5.5	Sugar Cane Fibre	70
5.6	Coconut Shell Fibre	73

5.7	Cellulose	76
5.8	Average Thermal Conductivity of Insulators	79
6.	CONCLUSION AND RECOMMENDATION	80
6.1	Recommendation	81
	REFERENCES	82
	APPENDICES	85

LIST OF TABLES

TABLE	TITLE	PAGE
2.1	Merits and demerits of the green buildings.	13
3.1	Local weather conditions during the monitoring periods.	21
3.2	Maximum and minimum superficial temperatures, in the exterior and the internal layer of the vegetal facade during the three selected days.	24
3.3	Maximum and minimum average outdoor temperature in Subrajaya from 1993 to 2005.	28
3.4	Thermal conductivity of bagasse fibres.	34
3.5	Thermal diffusivity for both thermal and chemical treated composites.	34
3.6	Comparison of life cycle analysis between common building materials.	39
3.7	Overall summary of previous works.	41
4.1	Ratios of raw materials and glue added to get the desired shapes.	47
4.2	Ratio of raw material with glue.	47
4.3	Reynolds number for air circulating in actual house and mini house model.	49
5.1	Positions of 7 different zone in Marcraft GT-7500 Mini House Model.	55
5.2	Three different condition to test the samples.	55
5.3	Area of insulators at each zone.	56
5.4	Indoor and outdoor temperature for polystyrene under Condition 1, 2 and 3.	58
5.5	Thermal conductivity of polystyrene for each condition.	59
5.6	Indoor and outdoor temperature for fibreglass under Condition 1, 2 and 3.	61

5.7	Thermal conductivity of fibreglass insulator for each condition.	62
5.8	Indoor and outdoor temperature for cotton under Condition 1, 2 and 3.	64
5.9	Thermal conductivity of cotton insulator for each condition.	65
5.10	Indoor and outdoor temperature for wool under Condition 1, 2 and 3.	67
5.11	Thermal conductivity of wool insulator for each condition.	68
5.12	Indoor and outdoor temperature for sugar cane fibre under Condition 1, 2 and 3.	70
5.13	Thermal conductivity of for sugar cane fibre each condition.	71
5.14	Indoor and outdoor temperature for coconut fibre under Condition 1, 2 and 3.	73
5.15	Thermal conductivity of for coconut fibre each condition.	74
5.16	Indoor and outdoor temperature for cellulose under Condition 1, 2 and 3.	76
5.17	Thermal conductivity of cellulose insulator for each condition.	77
5.18	Average thermal conductivity for each insulator.	79

LIST OF FIGURES

FIGURE	TITLE	PAGE
1.1	Extruded polystyrene foam as building wall insulation.	1
1.2	Project organization chart for Final Year Project.	5
2.1	Thermography inspections done by Department of Energy in Washington.	11
2.2	Properties needed in a green material.	14
3.1	Perceptual representation of the sedum species which are installed in each roof.	16
3.2	Sensors specification.	16
3.3	Average temperature gradient between green roof and white gravel roof for one hour intervals of the day.	17
3.4	Experimental building in this research.	20
3.5	Weather station to monitor the weather conditions.	20
3.6	Weather conditions during the three selected days: irradiation (a), temperature (b) and relative humidity (c).	23
3.7	Results for the green wall behaviour.	25
3.8	Coconut fibres in the test model.	29
3.9	Average rooftop surface and indoor room temperature May-July 2014.	29
3.10	Average indoor room air temperature for May-July 2014	30
3.11	Different of average indoor room air temperature between daytime and night time.	30
3.12	Surface of raw and treated bagasse fibres observed by SEM.	33

3.13	Evolution of the thermal conductivity based on the fibre content and fibre treatment.	33
3.14	Manufacture process of cellulose fibre insulator.	37
3.15	Relationship between thickness and density of cellulose fibre insulation.	39
4.1	Steps of cellulose sample preparation.	45
4.2	Steps of sugar cane and coconut Shell Sample Preparation.	46
4.3	Marcraft GT-7500 Mini House Model.	49
4.4	Sport light represent as sun to generate heat source.	50
4.5	Parts and dimensions of mini house model.	50
4.6	Illustration of how the Thermal Imagine Camera work.	51
4.7	Pico data logger TC-08.	52
4.8	Locations (red dots) of thermocouples will be installed.	53
4.9	Process of heat transfer conduction analysis.	53
4.10	Schematic diagram of HT10X and accessory HT11.	54
5.1	Polystyrene insulations tested under different conditions.	60
5.2	Fibreglass insulations tested under different conditions.	63
5.3	Cotton insulations tested under different conditions.	66
5.4	Wool insulations tested under different conditions.	69
5.5	Sugar cane fibre insulations tested under different conditions.	72
5.6	Coconut fibre insulations tested under different conditions.	75
5.7	Cellulose insulations tested under different conditions.	78

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Project flow chart	85
B	Project Gantt Chart	86
C	Appendix C1: Sample Reading from Pico Data Logger. Appendix C2: Thermal Images for Coconut Fibre Insulation.	87

LIST OF SYMBOLS

k	-	Thermal conductivity
ρ	-	Density
c	-	specific heat capacity
Q	-	Rate of heat conduction
ΔT	-	Temperature different
d / L	-	Material thickness
R	-	Thermal resistance of the material
K	-	Kelvin
$^{\circ}C$	-	Degree Celsius
κ	-	Thermal diffusivity
C_p	-	Specific heat
m	-	meter
W	-	Watt
kg	-	kilogram
k_{ave}	-	Average thermal conductivity
T	-	Temperature
A	-	Surface area of heat transfer
Re	-	Reynolds Number

LIST OF ABBREVIATIONS

3I	-	3 cm insulation layer
7I	-	7 cm insulation layer
CBAGB	-	Chemical treated bagasse fibre
CBAGP	-	Heat treated bagasse fibre
CFI	-	Cellulose fibre insulation
ExSTNI	-	External Surface Temperature No Insulation
GR	-	Green roof
GFO	-	Green facade optimization
HHW	-	Household waste
InSTNI	-	Internal Surface Temperature No Insulation
LCA	-	Life cycle analysis
NHIW	-	Non-hazardous industrial waste
NI	-	No insulation
SEM	-	Scanning Electron Microscope
UHI	-	Urban heat island
WG	-	White gravel

CHAPTER 1

INTRODUCTION

1.1 Background of Problem

Building insulation is defined as any object in a building, such as roof and wall are used as insulation for any purpose (Asdrubali, 2015). Majority of insulation in buildings is for thermal insulation purpose in Malaysia. Thermal insulator in buildings is one of the most important factor to achieve thermal comfort for its occupants. By installing the insulator in a building, it will reduce the unwanted heat loss or heat gain and also decrease the energy demands for heating or cooling systems. Generally, insulation can just refer to the insulation materials applied to slow down the heat transfer process from the outer wall to the inner wall, such as cellulose, rock wool, glass wool, wood fibre, plant fibre, cement, polystyrene, urethane foam and plant straw. Figure 1.1 shows the example of extruded polystyrene foam as wall insulation in building.



Figure 1.1: Extruded polystyrene foam as building wall insulation (KIMMU, 2017).

In Malaysia, the problem faced is the hot weather, where the greatest source of heat energy is mainly from solar radiation. Through the windows and doors, solar radiation is able to enter the buildings directly and heat up the wall to a higher temperature than the ambient and increasing the heat transfer through the building envelope and cause the room become hot and uncomfortable (Baker, 2013). In order to stay in comfortable room, refrigerated air conditioning is employed to solve the hot situation, then it is particularly important to seal the building envelope. Due to the dehumidification of air infiltration inside the room, it can significantly cause the wastes of energy. In Malaysia, most of the building designs are based on effective cross ventilation instead of installed air conditioning system to provide convective cooling to the room. Building construction and correct way of insulated materials installation on the wall of the buildings will ensure low conduction of heat transfer. This requires attention from contractor and designer.

The lesser the natural air flow into the building, the more mechanical ventilation required to ensure the thermal comfort of the occupants. High humidity in a room can be significant issue related to lack of airflow, construction material failure, condensation and encouraging growth of microbial such as bacteria and mould. These problems are incorporated with actively or passively air exchange systems. The higher the density of a material, the better it will conduct heat. For example, air is low density medium, hence, air is a very poor heat conductor and therefore can be a good insulator. Principle of insulation is to reduce the heat transfer conductive by using air spaces between fibres, plastic bubbles or foam and building's wall cavities. This is beneficial in an actively heated or cooled building, but can be a liability in a passively cooled building.

In this project, green waste materials is chosen to analyse and perform the heat transfer test. Green material is defined as biodegradable waste material, such as grass, plants, tree trimmings and fibre waste that can be diverted from landfills for recycling (Peterson,

2017). Statistic shows that millions tons of green waste is disposed of in landfills every year instead of being recycled or fully used. Besides shortens the life of landfills, landfilling green materials also contributes to Green House Gases emission. By applying green material in the building development, it may provide sustainable utilization of waste resources. Utilize of green material not only reduce the quantity of wastes, but also reduce the harmfulness to the environment. For example, in thermal energy storage system (TES) development in Pahang, Malaysia, in order to absorb the heat from outer wall to inner wall of a building, a form of green material is used as an insulator. The potential of heat absorber of the insulator is measured by its R-value. The greater the value of R-value, the better the heat insulation of the green material (Ali, 2013).

1.2 Problem Statement

The purpose of this study is to investigate the potential of waste or green materials as wall insulation for building. This study suits well with the current trend in building construction industry where the focus is on using environmental friendly and sustainable materials. This study will be conducted to find solutions to the following questions:

1. How is the thermal performance of green materials as wall insulation?
2. What are the effects of green materials as wall insulation on internal condition?
3. How efficient is the green materials as wall insulation compare to other types of wall insulation?

1.3 Objectives

The objectives of this project are:

1. To evaluate the thermal performance of green materials as wall insulation for residential housing.
2. To conduct a comparative analysis of the different green materials on how the interior and exterior of the house heats and cools.

1.4 Scope of Research

The scopes of this project are:

1. The experimental investigation will be conducted by using a mini house model.
2. The study will observe the temperature different between internal and external condition by installing different types of green materials.
3. For the temperature distribution during certain condition, the image will be recorded by using thermal infrared camera.
4. The heat transfer analysis will include the calculation of thermal conduction between the wall and green materials from outer surface to inner surface of the room.

1.5 Project Organization

Project organization is a structure that facilitates the coordination and implementation of the activities in the project. The main reason is to create a clear guideline and tidy structure when conduct the project (Diaz, 2007). Proper structured project organization can reduce confusion and uncertainty during project initiation phase is one of the main objectives of the project organization preparation. Proper design of project organization chart is essential to the project success. Figure 1.2 shows the project organization chart for Final Year Project.




Figure 1.2: Project organization chart for Final Year Project.

1.6 Important of the Work

The building construction industry is recently changing focus in using sustainable and green materials. With the abundance of the source, it is beneficial to utilize the application and observing its potential as wall insulation materials. This study is hoped to provide some prospect in using green materials as wall insulation. Besides that, the study tends to set as a benchmark study for further application of green materials in building construction.