



UNIVERSITI TEKNIKAL MALAYSIA MELAKA

**A STUDY ON MECHANICAL, PHYSICAL AND ENVIRONMENT
PROPERTIES FOR VARIED LENGTH ON THERMOPLASTICS
CORNSTARCH COMPOSITE REINFORCED BY UNTREATED
PINEAPPLE LEAF FIBRE**

This report is submitted in accordance with the requirement of the Universiti Teknikal Malaysia Melaka (UTeM) for the Bachelor of Mechanical Engineering Technology (Automotive) with Honours.

by

MUHAMMAD IKMAL KHAZANY BIN MOHD ASRI

B071510196

950102-03-5837

FACULTY OF MECHANICAL AND MANUFACTURING ENGINEERING
TECHNOLOGY

2018

BORANG PENGESAHAN STATUS LAPORAN PROJEK SARJANA MUDA

Tajuk: a study on mechanical, physical and environment properties for varied length on thermoplastics cornstarch composite reinforced by untreated pineapple leaf fibre

Sesi Pengajian: 2019

Saya **MUHAMMAD IKMAL KHAZANY BIN MOHD ASRI** mengaku membenarkan Laporan PSM ini disimpan di Perpustakaan Universiti Teknikal Malaysia Melaka (UTeM) dengan syarat-syarat kegunaan seperti berikut:

1. Laporan PSM adalah hak milik Universiti Teknikal Malaysia Melaka dan penulis.
2. Perpustakaan Universiti Teknikal Malaysia Melaka dibenarkan membuat salinan untuk tujuan pengajian sahaja dengan izin penulis.
3. Perpustakaan dibenarkan membuat salinan laporan PSM ini sebagai bahan pertukaran antara institusi pengajian tinggi.
4. ****Sila tandakan (X)**

SULIT*

Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia sebagaimana yang termaktub dalam

AKTA RAHSIA RASMI 1972.

TERHAD* Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan.

TIDAK
TERHAD

Yang benar,

Disahkan oleh penyelia:

.....

.....

MUHAMMAD IKMAL KHAZANY BIN

MOHD ASRI

NAZRI HUZAIMI BIN ZAKARIA

Alamat Tetap:

Cop Rasmi Penyelia

KAMPUNG GALOK CHETOK 17060

PASIR MAS KELANTAN

Tarikh:3/12/2018

Tarikh:

*Jika Laporan PSM ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali sebab dan tempoh laporan PSM ini

DECLARATION

I hereby, declared this report entitled a study on mechanical,physical and environment properties for varied length on thermoplastics cornstarch composite reinforced by untreated pineapple leaf fibre is the results of my own research except as cited in references.

Signature:

Author : MUHAMMAD IKMAL KHAZANY
BIN MOHD ASRI

Date:

APPROVAL

This report is submitted to the Faculty of Mechanical and Manufacturing Engineering Technology of Universiti Teknikal Malaysia Melaka (UTeM) as a partial fulfilment of the requirements for the degree of Bachelor of Mechanical Engineering Technology (Automotive) with Honours. The member of the supervisory is as follow:

Signature :

Supervisor : NAZRI HUZAIMI BIN ZAKARIA

ABSTRAK

Pada masa kini, serat semulajadi telah mendapat perhatian dari penyelidik dan telah menjadi isu penting bagi penyelesaian alternatif dalam menggantikan serat sintetik untuk menyelesaikan masalah ekologi dan persekitaran. Antara jenis serat semula jadi adalah serat daun nanas (PALF) yang telah dipilih sebagai serat semulajadi yang digunakan dalam kajian ini kerana ia mempunyai sifat mekanik yang lebih baik dan ia juga mempunyai kos pengeluaran yang rendah. Serat daun nanas dari jenis Josapines mempunyai kandungan selulosa yang tinggi dan mempunyai ciri-ciri mekanik yang sangat baik. Serat daun nanas jenis Josapines akan digunakan sebagai bahan bertetulang manakala tepung jagung sebagai pengikat. Dalam kajian ini, kesan kandungan PALF dan panjang serat pada komposisi PALF/TPCS akan dianalisis. Lima komposisi PALF yang berbeza ditetapkan pada 20,30, 40, 50, dan 60 wt% manakala panjang serat pula adalah 2mm dan 10mm. Sampel komposit dibuat dengan menggunakan teknik pengacuan kompresi dengan orientasi PALF secara rawak. Sampel akan menjalani tiga ujian yang berbeza, iaitu ujian mekanikal, ujian fizikal dan ujian alam sekitar. Oleh itu, hasil yang lebih tinggi untuk ujian mekanikal dari segi panjang serat ialah serat yang mempunyai panjang 10mm. Kekuatan tegangan pada beban serat 40% menunjukkan hasil yang tertinggi iaitu 10.51MPa manakala untuk hasil ujian lenturan yang tertinggi adalah pada beban gentian 50% iaitu 15.55MPa. Akhir sekali bagi ujian impak di mana hasil yang paling tinggi adalah pada beban gentian 20% iaitu 6.58 MPa.

ABSTRACT

Nowadays, natural fibres have received considerable attention from researchers and have become an important issue for alternative solutions in replacing the synthetic fibre to solving ecological and environmental problems. Among the many types of natural fibre available, pineapple leaf fibre (PALF) has been selected as the natural fibre used in this study because it has a better mechanical properties and it also has a low production cost. The PALF from the Josapines type has high cellulose content and has excellent mechanical properties. In this study the PALF of the Josapines type will be used as reinforced material while cornstarch is a binder. In this study, the effect of the content of PALF and the fibre length of the composition of PALF / TPCS will be analyzed. Five different PALF compositions are set at 20, 30, 40, 50, and 60 wt.% while the length of the fibres is 2mm and 10mm. The composite samples were fabricated by using compression moulding techniques with PALF randomized orientations. The sample will undergo three different tests, which are mechanical testing, physical testing and environmental testing. The highest result of mechanical testing in term of length is 10mm fibre length. For the tensile strength at 40% fibre loading shows the highest result which is 10.51MPa while for flexural testing the highest results at the 50% fibre loading 15.55MPa. Lastly, for impact testing higher result in the 20% fibre loading at 6.58MPa.

DEDICATION

This project report is lovingly dedicated to my beloved family members, especially to my father, Mohd Asri Bin Salleh and my mother, Sarimah Binti Yaacob who have been my constant source of inspiration. They have given me the drive and discipline to tackle any task with enthusiasm and determination. Without their loves and support this project would not have been made possible.

ACKNOWLEDGEMENTS

In the name of Allah, the Most Gracious, the Most Merciful. First and foremost, highest gratitude to Allah swt for granting me the strength, resilience, and knowledge to finish to complete the Final Year Project Report fluently and successfully. A lot of thanks to my family for supporting me through the whole processes of my Final Year Project. My deepest appreciation goes to my kind supervisor En Nazri Huzaimi Bin Zakaria for his enormous support, excellent guidance, caring, patience, providing full information and advice to finish up my report.

I would like to convey my great appreciation to Universiti Teknikal Malaysia Melaka (UTeM) for giving me an opportunity and chances to full fill my Final Year Project report. Besides, many thanks to committee members of Final Year Project, technician in Fasa B, En Mohd Rizal Bin Roosli that providing helps the whole process of this research nicely and smoothly. I am also using this opportunity to express my warm gratitude to everyone who supported me throughout this report. Last but not least, I would like to thank all of my friends for the knowledge sharing, their aspiring guidance and friendly advice to the successful completion of this report.

TABLE OF CONTENTS

	PAGE
TABLE OF CONTENTS	x
LIST OF TABLES	xiv
LIST OF FIGURES	xv
LIST OF APPENDICES	xix
LIST OF SYMBOLS	xx
LIST OF ABBREVIATIONS	xxi
CHAPTER 1 INTRODUCTION	22
1.1 Background	22
1.2 Problem Statement	24
1.3 Objectives	25
1.4 Scope	25
CHAPTER 2 LITERATURE REVIEW	26
2.1 Composite	26
2.2 Reinforcement	29
2.3 Natural fibre	30
2.4 Pineapple leaf fibre	39
2.5 Matrix (binder)	47

2.6	Starch	48
2.7	Thermoplastic Cornstarch	49
2.8	Plasticizer (glycerol)	51
2.9	Fibre extraction	51
2.10	Fibre length	56
2.11	Fibre loading	58
CHAPTER 3 METHODOLOGY		59
3.1	Flowchart	59
3.2	Preparation of Pineapple Leaf Fibre (PALF)	61
3.3	Matrix Preparation	62
3.4	Mixing process	65
3.5	Compression mould	67
3.6	Hot press process	67
3.7	Sample Cutting proses	68
3.8	Mechanical testing	69
3.8.1	Tensile Test Machine	70
3.8.2	Flexural testing machine	71
3.8.3	Impact test	73
3.9	Physical testing	74
3.9.1	Density Measurement.	74

3.9.2	Moisture content	75
3.9.3	Moisture absorption	75
3.9.4	Water absorption	76
3.10	Environment testing	77
3.10.1	Soil burial	77
3.10.2	Water solubility	78
CHAPTER 4		80
4.1	Mechanical testing	80
4.1.1	Tensile testing	80
4.1.2	Flexural testing	83
4.1.3	Impact testing	86
4.2	Physical testing	88
4.2.1	Density	88
4.2.2	Moisture content	89
4.2.3	Moisture absorption	91
4.2.4	Water absorption	94
4.3	Environment testing	96
4.3.1	Soil burial	96
4.3.2	Water solubility	99

CHAPTER 5	102
5.1 Conclusion	102
5.2 Recommendation	104
REFERENCES	105
APPENDIX	112

LIST OF TABLES

TABLE	TITLE	PAGE
Tabel 2. 1:	Properties of pineapple leaf fibre.	43
Table 3. 1:	Composition of PALF/TPCS (wt%)	65

LIST OF FIGURES

FIGURE	TITLE	PAGE
Figure 2. 1:	Classification of natural fibres	32
Figure 2. 3:	Classifications of biocomposites	36
Figure 2. 4:	The use of Natural Fibre for Automotive Composite in Austria and Germany 1996-2002	37
Figure 2. 5:	Categories of Natural Fibres.	38
Figure 2. 6:	Josapine pineapple.	42
Figure 2. 7:	Cross – section of Large Fibre Bundle of Josapine Leaf Fibre.	42
Figure 2. 8:	Various present and future applications of pineapple leaf.	45
Figure 2. 9:	Production of pineapple leaf fibre.	46
Figure 2. 10:	Scrapping Operations Roller.	52
Figure 2. 11:	Process of Extracting using Ceramic Plate.	53
Figure 2. 12:	The Kenaf Extractor Machine.	54
Figure 2. 13:	Dried Process of the fibre under Solar Drying House.	54
Figure 2. 14:	Manual shredding of pineapple leaf.	56
Figure 2. 15:	SEM of good adhesion between fibre and matrix (10 mm in fibre length)	57
Figure 2. 16:	SEM showing the fibre pull-out from matrix (2 mm in fibre length)	58
Figure 3. 1 :	Flow chart proses.	60

Figure 3. 2: Long PALF from Josaphine.	61
Figure 3. 3: Chopped PALF	62
Figure 3. 4: Cornstarch in powder form.	63
Figure 3. 5: Glycerol that added into cornstarch.	63
Figure 3. 6: Cornstarch and glycerol after mixed.	64
Figure 3. 7: TPCS wadding is refined with blender.	64
Figure 3. 8: A mixture between PALF and TPCS is put into a ball mill machine.	66
Figure 3. 9: Mixed PALF and TPCS are put into mould.	66
Figure 3. 10: The mould compress with compression moulding machine.	67
Figure 3. 11: The mould is inserted into the hot press machine.	68
Figure 3. 12: Sample after out from hot press machine.	69
Figure 3. 13: Sample after cutting process.	69
Figure 3. 14: Sample after cutting process.	69
Figure 3. 15: Instron 5690 Dual Column Testing System.	71
Figure 3. 16: Instron 4486 Universal Testing Machine (UTM).	72
Figure 3. 17: Pendulum Impact Test CEAST 9050.	73
Figure 3. 18: The Electronic Densimeter.	74
Figure 3. 19: Moisture absorption testing machine (GOTECH GT-705).	76
Figure 3. 20: Water absorption testing.	77
Figure 3. 21 : Soil burial testing.	78
Figure 3. 22 : Water solubility testing.	79

Figure 4. 1 : Graph of tensile strength (MPa) against fibre loading (wt%) for differences fibres length.	80
Figure 4. 2: Graph of tensile modulus (MPa) against fibres loading (wt%) for differences fibres length.	81
Figure 4. 3: Graph of flexural strength (MPa) against fibres loading (wt%) for differences fibres length.	83
Figure 4. 4: Graph of flexural modulus (MPa) against fibres loading (wt%) for differences fibres length.	84
Figure 4. 5: Graph of impact strength (kJ/m^2) against fibres loading (wt%) for differences fibres length.	86
Figure 4. 6: Graph of density measurement (g/cm^3) against fibre loading (wt %) for differences fibre length.	88
Figure 4. 7: Graph of moisture content (wt%) against fibre loading (wt%) for differences fibre length.	89
Figure 4. 8: Graph of moisture absorption (%) against days for 2mm fibre length in different fibre loading.	91
Figure 4. 9: Graph of moisture absorption (%) against days for 10mm fibre length in different fibre loading.	91
Figure 4. 10: Graph of moisture absorption (%) against days for 60% fibre loading in different fibre length.	92
Figure 4. 11: Graph of water absorption (%) against fibre loading (wt%) for time 0.5 hours.	94
Figure 4. 12: Graph of water absorption (%) against fibre loading (wt%) for time 2 hours.	94

Figure 4. 13: Graph of soil solubility against fibre loading (wt%) for 2mm fibre length for difference weeks.	96
Figure 4. 14: Graph of weight loss (%) against fibre loading (wt%) for 10mm fibre length for difference weeks.	97
Figure 4. 15: Graph of weight loss (%) against fibre loading (wt%) for 2 weeks for difference fibre length.	97
Figure 4. 16: Graph of weight loss (%) weight loss (%) against fibre loading (%) for 4 weeks for difference fibre length.	98
Figure 4. 17: Graph of water solubility (%) against fibre loading (%wt) in different fibre length.	100

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
Appendix 1	: ASTM D3039	112

LIST OF SYMBOLS

wt%	-	Weight percent
mm	-	Millimetre
T	-	Temperature
P	-	Pressure

LIST OF ABBREVIATIONS

PALF	Pineapple Leaf Fibre
GF	Glass Fibres
FRP	Fibre-Reinforced Plastics
CO₂	Carbon Dioxide
SH	Starch
TPCS	Thermoplastic Corn-Starch
NaOH	Sodium Hydroxide
LDPE	Low density polyethylene composite
RH	Relative humidity

CHAPTER 1

INTRODUCTION

1.1 Background

Composites are an idea of the combination of two or more natural resource materials basically made up of two materials that are fibre and matrix. Composites also are the combined result of more than one ingredient that will produce new material and the properties of the substance also increase from the original individual component. This combination will give unique properties, especially in mechanical properties where thus properties are different from their each material. As an example of natural composites growing with natural processes are bone, wood, and stone. The leaf themselves comprises natural fibres with good mechanical properties, strong, lightweight, biodegradable and cheaper to be used to create new composite materials. Based on all the natural fibres that exist, pineapple leaf fibre can produce good mechanical properties because it has high cellulose content (Mashitah, 2015).

The fibre function is used to reinforce the material and prevent it from being fragile. Fibre can be obtained from the extraction of natural fibres from various sources such as banana leaf, pineapple leaf, kenaf, bamboo and coconut. The matrix serves as a binder to hold the fibre in the composite. The source of the matrix can be obtained from starch, carbon, animal fats and other materials. With this combination will give a unique characteristic in mechanical properties where its properties is differ from each of its

ingredients. Ever since then humans have done an innovation where using composite materials to upgrade their lives. For example, combining mud with hay to obtain better bricks in terms of mechanical properties. In this case the mud would act as a binder for holding hay and this will increase the strength of the material (Mashitah, 2015).

Nowadays, natural fibres or natural composites have high potential to replace the fibreglass composite and they are also widely used as polymer composite reinforcement. Among the causes of it being chosen as the replacement of glass fibre reinforced composites is low cost, low density and has good mechanical properties compared to glass fibre reinforced composites. In addition, there are many benefits that can be obtained from natural fibres. For example, its benefits to the technology and the environment when it is widely used in inorganic composites because of natural fibres having high strength and good stiffness quality despite its low density. Natural fibre composites have been widely used by many industries today as one of the materials used in their production (Mashitah, 2015).

For example, bamboo fibres have been used worldwide by the automotive company mitshubishi to produce car interior. In addition, natural fibres use lower energy during production based on previous studies, so it provides a positive impact such as lower abrasion on the machine and there is no human health risk especially during inhalation. Besides, it is more environmentally friendly because it is biodegradable and contains less carbon dioxide. Other than that, the natural fibre strength will also increase if undergoing chemical treatment and it also has good thermal permeability based on previous studies (Mashitah,2015).

1.2 Problem Statement

Recently, scientific research has been conducted on natural plant fibres as a potential alternative source of fibres in fibre-reinforced plastics. Natural fibres have the potential to replace synthetic fibres because synthetic fibres will damage the environment and it is also non-renewable in turn creating severe pollution of the soil. In addition, synthetic fibre is not biodegradable and is not environmentally friendly, although it has good mechanical properties. In addition, natural fibres have many advantages as they can be recycled, widely available, biodegradable, renewable, they are also made of neutral carbon dioxide (CO₂) and most importantly, it does not have health risks when inhaled during the process. In Malaysia pineapple is also a focus for the industry, but only on its fruit. This causes the unused pineapple portion to be removed and burned as soon as possible. By doing so, it will add further pollution to the environment. The pineapple leaf which has been removed and burned actually has good fibre sources and can be used in industrial use.

Among the various plant fibres, fibre with high cellulose content is the pineapple leaf fibre (PALF) obtained from the Josapine pineapple leaf. PALF has shown excellent mechanical properties and is highly potential to be used as reinforcement in polymer composites because it contains rich cellulose content of more than 70%. As a result of a combination of pineapple leaf fibre used as a reinforcing material and starch based composites as a matrix material, has produced a highly productive PALF composite for plastic industrial products because of its good mechanical properties.