



## **UNIVERSITI TEKNIKAL MALAYSIA MELAKA**

### **THE INVESTIGATION ON MECHANICAL, PHYSICAL AND ENVIRONMENT PROPERTIES FOR DIFFERENT METHOD OF FABRICATION ON CORNSTARCH COMPOSTIES REINFORCED BY PINEAPPLE LEAF FIBRE**

This report is submitted in accordance with the requirement of the Universiti Teknikal Malaysia Melaka (UTeM) for the Bachelor of Mechanical Engineering Technology (Automotive) with Honours.

by

**MUHAMMAD NUR FUDHAIL BIN AZMI**

**B071510844**

**940914145215**

FACULTY OF MECHANICAL AND MANUFACTURING ENGINEERING  
TECHNOLOGY

2018

**BORANG PENGESAHAN STATUS LAPORAN PROJEK SARJANA MUDA**

Tajuk: THE INVESTIGATION ON MECHANICAL, PHYSICAL AND ENVIRONMENT PROPERTIES FOR DIFFERENT METHOD OF FABRICATION ON CORNSTARCH COMPOSTIES REINFORCED BY PINEAPPLE LEAF FIBRE

Sesi Pengajian: 2018

Saya **MUHAMMAD NUR FUDHAIL BIN AZMI** mengaku membenarkan Laporan PSM ini disimpan di Perpustakaan Universiti Teknikal Malaysia Melaka (UTeM) dengan syarat-syarat kegunaan seperti berikut:

1. Laporan PSM adalah hak milik Universiti Teknikal Malaysia Melaka dan penulis.
2. Perpustakaan Universiti Teknikal Malaysia Melaka dibenarkan membuat salinan untuk tujuan pengajian sahaja dengan izin penulis.
3. Perpustakaan dibenarkan membuat salinan laporan PSM ini sebagai bahan pertukaran antara institusi pengajian tinggi.
4. \*\*Sila tandakan (X)

SULIT\* Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia sebagaimana yang termaktub dalam AKTA RAHSIA RASMI 1972.

TERHAD\* Mengandungi maklumat TERHAD yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan.

TIDAK TERHAD

Yang benar,

Disahkan oleh penyelia:

.....  
MUHAMMAD NUR FUDHAIL BIN  
AZMI

.....  
NAZRI HUZAIMI BIN ZAKARIA

Alamat Tetap:

Cop Rasmi Penyelia

X

X

X

Tarikh:

Tarikh:

\*Jika Laporan PSM ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali sebab dan tempoh laporan PSM ini

## DECLARATION

I hereby, declared this report entitled THE INVESTIGATION ON MECHANICAL, PHYSICAL AND ENVIRONMENT PROPERTIES FOR DIFFERENT METHOD OF FABRICATION ON CORNSTARCH COMPOSTIES REINFORCED BY PINEAPPLE LEAF FIBRE is the results of my own research except as cited in references.

Signature: .....

Author : MUHAMMAD NUR FUDHAIL BIN  
AZMI

Date:

## **APPROVAL**

This report is submitted to the Faculty of Mechanical and Manufacturing Engineering Technology of Universiti Teknikal Malaysia Melaka (UTeM) as a partial fulfilment of the requirements for the degree of Bachelor of Mechanical Engineering Technology (Automotive) with Honours. The member of the supervisory is as follow:

Signature: .....

Supervisor:       NAZRI HUZAIMI BIN ZAKARIA

## **ABSTRACT**

This research intends to ensure the compatibility of using thermoplastic cornstarch (TPCS) and reinforced by pineapple leaf fibre (PALF) as a replacement for synthetic fibre. Besides that, this research also to study the effect on the properties by using different methods of preparations TPCS reinforced by PALF composites. The variable of testing has been used to the sample of PALF/TPCS which is mechanical, physical and environment as it gives a different result of each method of preparation. Furthermore, by using the different compositions of PALF / TPCS which is 20:80, 30:70, 40:60, 50:50 and 60:40, it is also affected the results of mechanical, physical and environmental testing. For the mechanical testing such as tensile test, it shows that the mixture method has the higher result of tensile strength (10.51 MPa) compared to the layer method (9.69 MPa) at 40:60 wt%. As for the conclusion, it can be concluded that the sample that are going through mixture method has the highest and best result in mechanical, physical and environmental properties compare to the sample that are fabricated by using layer method.

## ABSTRAK

Kajian ini bertujuan untuk memastikan kesesuaian penggunaan tepung jagung termoplastik (TPCS) dan diperkuat oleh serat daun nenas (PALF) sebagai pengganti serat sintetik. Selain itu, kajian ini juga bertujuan untuk mempelajari kesan ke atas sifat – sifat penggunaan TPCS yang diperkuat oleh PALF menggunakan kaedah penyediaan yang berbeza. Pelbagai jenis ujian telah dijalankan terhadap sampel PALF/TPCS ini seperti ujian mekanikal, fizikal dan persekitaran yang mana telah memberikan keputusan yang berbeza bagi setiap kaedah penyediaan. Penggunaan komposisi PALF/TPCS yang berlainan iaitu 20:80, 30:70, 40:60, 50:50 dan 60:40 juga telah mempengaruhi keputusan yang dihasilkan oleh ujian mekanikal, fizikal dan persekitaran. Di dalam ujian mekanikal seperti ujian tegangan, keputusan menunjukkan bahawa kaedah campuran (mixture) telah menghasilkan keputusan yang lebih tinggi iaitu 10.51 MPa berbanding keputusan menggunakan kaedah lapisan (laminat) iaitu 9.69 MPa pada komposisi 40:60 wt%. Oleh itu, hasil daripada kajian ini dapat disimpulkan bahawa sifat-sifat PALF/TPCS komposit yang dihasilkan melalui kaedah campuran (mixture) telah memberikan keputusan yang lebih baik bagi ujian mekanikal, fizikal dan persekitaran berbanding keputusan yang dihasilkan oleh kaedah penyediaan melalui lapisan (laminat).

## **DEDICATION**

This report is dedicated to my beloved parents, my family members and my friends who always give me full support and encourages completing my final year project. In addition, my final year group mates who giving me guidance and assists during the project.



## **ACKNOWLEDGEMENTS**

First and foremost, I would like to grab this chance to express my sincere gratitude to my supervisor, En. Nazri Huzaimi bin Zakaria from the Faculty of Mechanical and Manufacturing Engineering Technology, Universiti Teknikal Malaysia Melaka (UTeM) for his essential guidance, support and encouragement towards the completion of the final year project report. Special thanks to UTeM for giving fund required to complete this project. In addition, I would like to thank the technicians from a mechanical testing laboratory at the Faculty of Mechanical and Manufacturing Engineering Technology sincerely. Finally, I would like to thank my beloved parents, siblings and my friends for providing mental support throughout this final year project. Thanks to everyone who have been a significant part in the realization of this project.

# TABLE OF CONTENTS

	<b>PAGE</b>
TABLE OF CONTENTS	x
LIST OF TABLES	xv
LIST OF FIGURES	xvi
LIST OF APPENDICES	xix
LIST OF ABBREVIATIONS	xx
<b>CHAPTER 1      INTRODUCTION</b>	<b>1</b>
1.1      Overview	1
1.2      Objective	2
1.3      Problem Statement	3
1.4      Scope	4
<b>CHAPTER 2      LITERATURE REVIEW</b>	<b>5</b>
2.1      Introduction	5
2.2      Composites	6
2.3      Reinforcement	7
2.4      Natural Fibre	8

2.5	Pineapple Leaf	12
2.6	Fibre Extraction Method	16
2.7	Matrix (Binder)	18
2.8	Starch	19
2.9	Corn-starch	20
2.10	Plasticizer	21
2.11	Preparation Method	22
2.11.1	Mixture Method	22
2.11.2	Layer (Laminate) Method	22
2.12	Testing Method	23
2.12.1	Mechanical Testing	23
2.12.1.1	Tensile Testing	23
2.12.1.2	Flexural Method	24
2.12.1.3	Impact Test	24
2.12.2	Physical Testing	25
2.12.2.1	Density Measurement	25
2.12.2.2	Moisture Content	26
2.12.2.3	Moisture Absorption	26
2.12.2.4	Water Absorption	27
2.12.3	Environment Testing	27

2.12.3.1	Soil Solubility	27
2.12.3.2	Water Solubility	28
<b>CHAPTER 3</b>	<b>METHODOLOGY</b>	<b>29</b>
3.1	Introduction	29
3.2	Flowchart	30
3.3	Processing Method	32
3.3.1	Preparation of Pineapple Leaf Fibre (PALF)	32
3.3.2	Matrix Preparation	35
3.3.3	Compression Moulding	36
3.3.4	Cutting Process	39
3.4	Mechanical testing	40
3.4.1	Tensile Test Machine	40
3.4.2	Flexural Testing Machine	41
3.4.3	Impact Test	43
3.5	Physical Testing	44
3.5.1	Density Measurement	44
3.5.2	Water absorption	45
3.5.3	Moisture absorption	45
3.5.4	Moisture content	46
3.6	Environment Testing	47

3.6.1	Soil burial	47
3.6.2	Water Solubility	48
<b>CHAPTER 4</b>	<b>RESULT AND DISCUSSION</b>	<b>50</b>
4.1	Sample Result	50
4.2	Mechanical Testing	53
4.2.1	Tensile Testing	53
4.2.2	Flexural Testing	56
4.2.3	Impact Testing	59
4.3	Physical Testing	61
4.3.1	Density Measurement	61
4.3.2	Moisture Content	63
4.3.3	Water Absorption	65
4.3.4	Moisture Absorption	67
4.4	Environment Testing	71
4.4.1	Soil Solubility	71
4.4.2	Water Solubility	75
<b>CHAPTER 5</b>	<b>CONCLUSION AND RECOMMENDATION</b>	<b>77</b>
5.1	Conclusion	77
5.2	Recommendation	78

<b>REFERENCES</b>	<b>80</b>
<b>APPENDIX</b>	<b>85</b>

## LIST OF TABLES

TABLE	TITLE	PAGE
	Table 2.1: Properties of pineapple leaf fibre (Kasim et al., 2015)	15

## LIST OF FIGURES

<b>FIGURE</b>	<b>TITLE</b>	<b>PAGE</b>
Figure 2.1:	Josephine pineapple (Mohamed et al., 2009)	11
Figure 2.2 :	Categories of Natural Fibres (Munirah, Abdul Razak and Hassan, 2007)	12
Figure 2.3 :	Production of pineapple leaf fibre based on (Asim et al., 2015)	14
Figure 2.4:	Mechanical PALF extractor (Jose, Salim and Ammayappan, 2016)	17
Figure 2.5:	Process of Extracting using Ceramic Plate (Kannojiya et al., 2013)	18
Figure 3.1:	Flowchart	31
Figure 3.2:	Rapid Two-roll Mill Machine Used for Remove Water and Composite Compounding	33
Figure 3.3:	PALF Photos: (a) Long PALF Extracted from Raw Leaf (b) Chopped PALF	34
Figure 3.4:	Corn-starch powder form	35
Figure 3.5:	Glycerol that added into corn-starch	36
Figure 3.6:	The ball mill machine for mixing technique before put into the mould	37
Figure 3.7:	The sample by using mixing technique in the mould before compression process	37
Figure 3.8:	The sample by using sandwich/ lamina technique in the mould before compression process	38
Figure 3.9:	The sample in the mould before compression process	38



Figure 3.10: Hot Press Machine	39
Figure 3.11: Dimension of the specimen according to the standard needed.	40
Figure 3.12: Instron 5690 Dual Column Testing System	41
Figure 3.13: Instron 4486 Universal Testing Machine (UTM)	42
Figure 3.14: The Electronic Densimeter	44
Figure 3.15: The Humidity Chamber	46
Figure 4.1: The sample of thermoplastic corn starch (TPCS) reinforced by PALF composites	50
Figure 4.2 : The samples in the mould before the hot press compression process	51
Figure 4.3: The hot press machine used in this experiment	51
Figure 4.4: Graph of tensile strength (MPa) against fibre loading (wt%) for 10mm differences method samples	53
Figure 4.5: Graph of tensile modulus (MPa) against fibres loading (wt%) for 10mm differences method samples	53
Figure 4.6: Graph of flexural strength (MPa) against fibres loading (wt%) for 10mm differences method samples	56
Figure 4.7: Graph of flexural modulus (MPa) against fibres loading (wt%) for 10mm differences method samples	56
Figure 4.8: Graph of impact strength (kJ/m <sup>2</sup> ) against fibres loading (wt%) for 10mm differences method samples	59
Figure 4.9: Graph of density measurement (g/cm <sup>3</sup> ) against fibre loading (wt%) for 10mm differences method samples	61
Figure 4.10: Graph of moisture content (wt%) against fibre loading (wt%) for 10mm differences method samples	63

Figure 4.11: Graph of water absorption (wt%) against fibre loading (wt%) for fibre length 10mm in different method for 0.5 hours	65
Figure 4.12: Graph of water absorption (wt%) against fibre loading (wt%) for fibre length 10mm in different method for 2 hours	65
Figure 4.13: Graph of moisture absorption (wt%) against days for fibre length 10mm in (mixture) method	67
Figure 4.14 : Graph of moisture absorption (wt%) against days for fibre length 10mm in (layer) method	68
Figure 4.15 : Graph of moisture absorption (wt%) against days for fibre length 10mm in different method (Mixture and Layer)	69
Figure 4.16: Graph of soil solubility (wt%) against fibre loading (wt%) for fibre length 10mm in different method samples (Mixture and Layer) for 2 weeks	71
Figure 4.17 : Graph of soil solubility (wt%) against fibre loading (wt%) for fibre length 10mm in different method samples for 4 weeks	71
Figure 4.18: Graph of soil solubility (wt%) against fibre loading (wt%) for fibre length 10mm (mixture) for 2 weeks and 4 weeks	73
Figure 4.19: Graph of soil solubility (wt%) against fibre loading (wt%) for fibre length 10mm (layer) for 2 weeks and 4 weeks	73
Figure 4.20: Graph of water solubility (wt%) against fibre loading (wt%) for fibre length 10mm in different method samples	75

## LIST OF APPENDICES

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
<b>Appendix A:</b>	ASTM D3039	86
<b>Appendix B:</b>	ASTM D2502, ASTM D790	88

## LIST OF ABBREVIATIONS

<b>PALF</b>	Pineapple leaf fibre
<b>TPCS</b>	Thermoplastic cornstarch
<b>FRP</b>	Fibre reinforced polymer
<b>GF</b>	Glass fibre
<b>SPS</b>	Sugar palm starch
<b>HIPS</b>	High impact polystyrene

# CHAPTER 1

## INTRODUCTION

### 1.1 Overview

The idea of combining two or more natural resource materials that are basically made up of Fibres/Reinforced and Matrix/Binder is called Green composites. In which the mixture of both materials will infuse unique properties and those properties will be differ than each material. Banana leaf, pineapple leaf, kenaf, bamboo and coconut are known to be the various sources of extradition of natural fibre that are the examples of Fibre/Reinforced materials. As for matrix/binder materials, the examples are starch, epoxy and polypropylene. For centuries, the composite materials have been used to enhance life condition of a mankind. As per example, in order to ensure mud brick is more solid or durable, it will be combined with straw and the mud has become the glue that sticks the straw together. This combination will ensure the construction of the buildings become firmer.

As in present day, natural fibre or green composites are being used frequently as a backup in polymer composites and have high potential in substituting the fibre glass reinforced composites This is due to their low cost, low density but have good sets of mechanical properties compared to fibre glass reinforced composites.

Fact is, natural fibre offers various technological and environmental advantages when it is used as backup, composite such as high strength and good in stiffness feature even though it has a low density. Furthermore, natural fibre originated from various resources that contained fibre such as plant itself; bamboo fibre, coconut fibre, pineapple

leaf fibre, hemp fibre and jute fibre. Nowadays there are a lot of industrial companies that changed into using the natural fibre composites.

For example, Mitsubishi, a worldwide automotive company, is trying to use bamboo fibre to produce internal cars and more. In addition, from previous studies that have been done, it shows that natural fibres use lower energy during production, resulting in lower abrasion to the machine and there is no risk to human health especially during inhalation. In addition, based on previous studies, natural fibres also have good thermal permeability and fibre strength will increase if they undergo chemical treatment. Furthermore, it also contains less carbon dioxide and biodegradable replication that makes it more environmentally friendly on earth.

## **1.2 Objective**

The objectives of this project are:

1. To study the effect of properties by using different method of fabrication of thermoplastic cornstarch (TPCS) and reinforced by pineapple leaf fibre (PALF).
2. To determine the effect of using TPCS and reinforced by PALF.
3. To fabricate the composite of PALF/TPCS by using laminate method.
4. To fabricate the composite of PALF/TPCS by using mixture method.

### 1.3 Problem Statement

Lately, scientific researchers have identified natural plant fibre as a replacement to glass fibre (GF) in fibre-reinforced polymer (FRP). Natural fibres have the potential to replace synthetic fibres because synthetic fibres will damage the environment and it is also non-renewable in turn creating severe pollution of the soil. In addition, synthetic fibre is not biodegradable and is not environmentally friendly, although it has good mechanical properties. In addition, natural fibres have many advantages as they can be recycled, widely available, biodegradable, and renewable they are also made of neutral carbon dioxide ( $CO_2$ ) and most importantly it does not have health risks when inhaled during the process. In Malaysia, pineapple is also a focus for the industry, but only on its fruit. This causes the unused pineapple portion to be removed and burned as soon as possible. By doing so, it will add further pollution to the environment. The pineapple leaves which have been removed and burned have good fibre sources and can be used in industrial use.

Among the various plant fibres, fibre with high cellulose content is the pineapple leaf fibre (PALF) obtained from Josephine pineapple leaves. PALF has shown excellent mechanical properties and is highly potential to be used as reinforcement in polymer composites because it contains rich cellulose content of more than 70 wt%. As a result of a combination of pineapple leaf fibre used as a reinforcing material and starch-based composites as a matrix material, has produced a highly productive PALF composite for plastic industrial products because of its good mechanical properties.

## 1.4 Scope

In this study, the effect of PALF loading and PALF fibre length on PALF / TPCS composite mechanical properties will be studied. The effect of different method during preparation of PALF/ TPCS will also be studied. The different method will be given a different result by using a testing method such as tensile test, hardness test, flexural test and density measurement. The composition ratio in PALF / TPCS composites has been set at 20:80, 30:70, 40:60, 50:50, 60:40 wt%. Besides that, for PALF length has been fixed at 10mm. The mechanical properties of PALF/TPCS composite will be determined using the tensile, impact and flexural test. Other than that, physical testing also will be conducted with moisture content, water absorption and moisture absorption. The environmental testing also will be conducted with soil solubility and water solubility.