

Faculty of Electrical and Electronic Engineering Technology



UNIVERSITI TEKNIKAL MALAYSIA MELAKA

HASIF BIN MOHAMAD

Bachelor of Electrical Engineering Technology (Industrial Power) with Honours

2022

INVESTIGATION OF NEM SOLAR PV POWER INTERGRATION ONTO CENTRAL GRID IN MALAYSIA

HASIF BIN MOHAMAD

A project report submitted in partial fulfillment of the requirements for the degree of Bachelor of Electrical Engineering Technology (Industrial Power) with Honours



UNIVERSITI TEKNIKAL MALAYSIA MELAKA

2022



UNIVERSITI TEKNIKAL MALAYSIA MELAKA FAKULTI TEKNOLOGI KEJUTERAAN ELEKTRIK DAN ELEKTRONIK

BORANG PENGESAHAN STATUS LAPORAN PROJEK SARJANA MUDA II

Tajuk Projek : INVESTIGATION OF NEM SOLAR PV POWER INTERGRATION ONTO CENTRAL GRID IN MALAYSIA

Sesi Pengajian: 2022/2023-1

Saya Hasif Bin Mohamad mengaku membenarkan laporan Projek Sarjana Muda ini disimpan di Perpustakaan dengan syarat-syarat kegunaan seperti berikut:

- 1. Laporan adalah hakmilik Universiti Teknikal Malaysia Melaka.
- 2. Perpustakaan dibenarkan membuat salinan untuk tujuan pengajian sahaja.
- 3. Perpustakaan dibenarkan membuat salinan laporan ini sebagai bahan pertukaran antara institusi pengajian tinggi.
- 4. Sila tandakan (✓):

(Mengandungi maklumat yang berdarjah keselamatan atau kepentingan Malaysia SULIT* seperti yang termaktub di dalam AKTA RAHSIA RASMI 1972) (Mengandungi maklumat terhad yang telah ditentukan oleh organisasi/badan di mana penyelidikan dijalankan) TIDAK TERHAD oleh: (COP DAN TANDATANGAN PENYELIA) (TANDATANGAN PENULIS) Alamat Tetap: **CHE WAN MOHD FAIZAL BIN CHE WAN MOHD ZALANI** No. 51, Jalan KI 1, Jurutera Pengajar Jabatan Teknologi Kejuruteraan Elektrik Fakulti Teknologi Kejuruteraan Elektrik Dan Elektronik Universiti Teknikal Malaysia Melaka Taman Krubong Indah. 75260 Melaka. Tarikh: 16/2/2023 Tarikh: 25/1/2023

*CATATAN: Jika laporan ini SULIT atau TERHAD, sila lampirkan surat daripada pihak berkuasa/organisasi berkenaan dengan menyatakan sekali tempoh laporan ini perlu dikelaskan sebagai SULIT atau TERHAD.

DECLARATION

I declare that this project report entitled "Investigation Of Nem Solar Pv Power Intergration Onto Central Grid In Malaysia" is the result of my own research except as cited in the references. The project report has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

LAYSIA Signature BIN MOHAMAD Student Name HASIF 25 JANUARI 2023 Date • UNIVERSITI TEKNIKAL MALAYSIA MELAKA

APPROVAL

I hereby declare that I have checked this project report and in my opinion, this project report is adequate in terms of scope and quality for the award of the degree of Bachelor of Electrical Engineering Technology (Industrial Power) with Honours

| Signature : |
|---|
| Supervisor Name : |
| Che wan Mono Faizar bin Che wan Mond Zalani |
| Late : 16/2/2023 |
| a salar |
| اونيوم سيتي تيڪنيڪل مليسيا ملاك |
| Co-Supervisor NIVERSITI TEKNIKAL MALAYSIA MELAKA |
| Name (if any) |
| Date : |
| |

DEDICATION

Dedicated to

My parents: Mohamad bin Kandar (Deceased). May Allah forgive his soul. Marldia binti Hassan. May all your remaining years bless with health and happiness.

> *My wife : Rozita Mohd. Shahri. May Allah bless our little family.*

My kids : Daie, Dini, Daud and Dira, May all the success in the world and the after be with you.



ABSTRACT

Installation of solar PV system in Malaysia is at all-time high due to exponential cost reduction and government backing of solar PV generation through scheme as FiT, NEM, and SELCO which drive solar PV growth in generation mix. This research was aimed to investigate and analyze the effects of grid connected solar PV generation on frequency fluctuations, voltage fluctuation, THD_V and voltage flickers, in parallels with studying protections applied in ensuring negatives impacts from grid connected solar PV is negated. Mix methods methodology which encompass site visits, field interviews, parameters measurement on sites using PQA, data analysis using statistical methods consisting Pearson correlation analysis, process capability analysis and descriptive analysis, simulations of solar PV systems using PVSYT, and comparing results through standards of ESAH, MGC and NEM Guidelines was done in order to accomplish the objective of the research. The results found out that solar PV system installed was in compliance with protections standards outline by authorities and utilities providers such as ST, SEDA and TNB. The impact of grid connected solar PV to the grid power quality and stability was minimal. From the analysis, the correlation between power generated by solar PV to PQ could be determine. However, loads dynamics had more directs impacts to the grid stability compared to solar PV systems In conclusion, a solar PV system with all the protection and mitigation requirement was in placed in accordance to the standards outlined, the solar PV output PQ was controlled in precise, accurate and within specification manner. Hence, providing minimum impact to the system frequency fluctuations, voltage fluctuation, THD_V and voltage flickers compared to loads demand dynamics.

ABSTRAK

Pemasangan sistem PV solar di Malaysia mencatatkan pertumbuhan tertinggi disebabkan pengurangan kos dan sokongan kerajaan bagi penjanaan solar PV melalui skim FiT, NEM dan SELCO yang memacu pertumbuhan PV solar. Penyelidikan ini bertujuan untuk menyiasat dan menganalisis kesan penjanaan PV solar yang bersambung ke grid kepada perubahan frekuensi, perubahan voltan, THD_V dan kelipan voltan, selari dengan mengkaji sistem perlindungan yang digunakan dalam memastikan tiada kesan negatif daripada penjanaan PV solar kepada grid. Kaedah metodologi campuran yang merangkumi lawatan tapak, temu bual lapangan, pengukuran parameter menggunakan POA, analisis data menggunakan kaedah statistik yang terdiri daripada analisis korelasi Pearson, analisis keupayaan proses dan analisis deskriptif, simulasi sistem PV solar menggunakan PVSYT, dan membandingkan keputusan melalui piawaian ESAH, MGC dan Garis Panduan NEM telah dilakukan bagi mencapai objektif penyelidikan. Didapati sistem PV solar yang dipasang di ANM adalah mematuhi piawaian perlindungan yang digariskan oleh pihak berkuasa dan pembekal utiliti seperti ST, SEDA dan TNB. Kesan PV solar kepada kualiti dan kestabilan kuasa grid adalah minimum. Daripada analisis yang dilakukan, korelasi antara kuasa yang dijana oleh PV solar dengan PQ dapat ditentukan. Kesimpulannya, sistem PV solar yang dilengkapi perlindungan dan mitigasi mengikut piawaian yang digariskan, dapat mengawal PQ keluaran PV solar dengan tepat dan mengikut spesifikasi. Serta, memberikan impak minimum kepada turun naik frekuensi sistem, turun naik voltan, THDV dan kelipan voltan berbanding dengan kesan akibat dinamik bekalan dan permintaan kepada beban.

ACKNOWLEDGEMENTS

First and foremost, thank you Allah, all praise to Allah the Almighty, the Most Gracious, and the Most Merciful for His blessing given to me during my study and in completing this thesis. May Allah's blessing goes to His final Prophet Muhammad (peace be up on him), his family and his companions.

I would like to express my gratitude to Universiti Teknikal Malaysia Melaka (UTeM) and Agensi Nuklear Malaysia (ANM) for the opportunity to conduct this research. Abundances thank you to my supervisor, Mr. Che Wan Mohd. Faizal bin Che Wan Mohd Zalani, FTKEE, UTeM and industrial-supervisor, Mr. Mohd. Hanafiah bin Chik, BKJ, ANM for their precious guidance, words of wisdom and patient throughout this project.

My highest appreciation goes to my wife Rozita Mohd Shahri, to my kids Daie, Dini, Daud and Dira, to my parents Mohamad bin Kandar (deceased) and Marldia binti Hassan, parent's in-law, and family members for their love, support and prayer during the period of my study.

Finally, I would like to thank all the staffs at the ANM Chargeman Mr. Zulkifli, Senior Technical Assistant Mr. Ruzaini, fellow colleagues and classmates, the Faculty members, as well as other individuals who are not listed here for being co-operative and helpful.

TABLE OF CONTENTS

| | PAGE |
|--|---------------|
| DECLARATION | |
| APPROVAL | |
| DEDICATIONS | |
| ABSTRACT | i |
| ABSTRAK | ii |
| ACKNOWLEDGEMENTS | iii |
| TABLE OF CONTENTS | iv |
| LIST OF TABLES | vii |
| LIST OF FIGURES | ix |
| LIST OF SYMBOLS | XV |
| LIST OF ABBREVIATIONS | xvi |
| LIST OF APPENDICES | xvii |
| اونيوم سيني تيڪ INTRODUCTION اونيوم سيني آيا 1.1 Background | 1 1 |
| 1.2 Problem Statement TI TEKNIKAL MALAYSIA MELAKA 1.3 Project Objectives | 7 8 |
| 1.4 Scopes of Project | 9 |
| 1.4.1 Paramaters of Power Quality 1.4.2 Connection Configuration To The Grid | 9 10 |
| 1.4.3 Methodology Selection | 10 |
| CHAPTER 2 LITERATURE REVIEW | 12 |
| 2.2 Background | 12 |
| 2.3 Frequency Stability Literature Review | 14 |
| 2.4 Total Harmonic Distortion (THD) Literature Review 2.5 Mitigation for Frequency Stability and Total Harmonics Distortion | 21 |
| 2.6 Voltage Fluctuation Literature Review | 24 |
| 2.7 Voltage Flickers Literature Review | 31 |
| 2.8 Mitigation of Voltage Fluctuation and Voltage Flicker | 34 |
| 2.9 Comparison Table Between Literature 2.10 Research Gap and Suggestion | 37 70 |
| 2.10 1 Overview of Research Gap and Suggestion | 40 |
| 2.10.2 Research Gap by Literature | 41 |

| | 2.10.3 | Summary of Research Gap in Table Form | 44 | |
|------|---------|---|-----|--|
| CHAF | PTER 3 | METHODOLOGY | 46 | |
| 3.1 | Introdu | uction | 46 | |
| 3.2 | Metho | dology | 46 | |
| 3.3 | Locati | on of Study | 47 | |
| 3.4 | Power | Quality Parameters Measurement and Analysis | 48 | |
| | 3.4.1 | Frequency Fluctuation Measurement and Analysis Process Flow | 51 | |
| | 3.4.2 | Voltage Total Harmonics Distortion (THD _V) Measurement ar | nd | |
| | | Analysis Process. | 53 | |
| | 3.4.3 | Voltage Fluctuation Measurement and Analysis Process | 55 | |
| | 3.4.4 | Voltage Flickers Measurement and Analysis Proscess | 57 | |
| 3.5 | Equip | ment, Tools and Application Suggestion | 59 | |
| | 3.5.1 | Power Quality Analyzer (PQA). | 59 | |
| | 3.5.2 | Interfacing and Analytical Application. | 61 | |
| | 3.5.3 | Analysis Method and Application | 65 | |
| | 3.5.4 | Meteorological Data | 74 | |
| 0.4 | 3.5.5 | Simulation Application | 76 | |
| 3.6 | Limita | tion of proposed methodology | 77 | |
| СНАЕ | PTER 4 | RESULTS, ANALYSIS AND DISCUSSIONS | 78 | |
| 4 1 | Introdu | inction | 78 | |
| 4.2 | Result | | 79 | |
| 1.2 | 4.2.1 | Distribution System and Solar PV System Configuration ar | nd | |
| | 1.2.1 | Specification | 79 | |
| | 4.2.2 | Solar Radiation Instensity and Power Generated Result | 85 | |
| | 4.2.3 | Frequency Fluctuation Result | 87 | |
| | 4.2.4 | Voltage Fluctuation Result | 88 | |
| | 4.2.5 | Voltage Total Harmonic Distortion (THDy) Result | 90 | |
| | 4.2.6 | Voltage Flickers Fluctuation Results AYSIA MELAKA | 92 | |
| 4.3 | Analys | sis Result | 96 | |
| | 4.3.1 | Power Quality Discriptive Analysis | 96 | |
| | | 4.3.1.1 TMSB 1 | 96 | |
| | | 4.3.1.2 TMSB 2 | 98 | |
| | | 4.3.1.3 TMSB 3 | 100 | |
| | 4.3.2 | Power Quality Process Capability Analysis | 102 | |
| | | 4.3.2.1 Frequency Process Capability Analysis | 102 | |
| | | 4.3.2.2 Voltage Fluctuation Process Capability Analysis | 104 | |
| | | 4.3.2.3 THD _v Process Capability Analysis | 108 | |
| | | 4.3.2.4 Voltage Flickers Process Capability Analysis | 111 | |
| | 4.3.3 | Power Quality Pearson Correlation Analysis | 117 | |
| | | 4.3.3.1 TMSB 1 | 117 | |
| | | 4.3.3.2 TMSB 2 | 118 | |
| | | 4.3.3.3 TMSB 3 | 120 | |
| 4.4 | Discus | ssion | 122 | |
| | 4.4.1 | Frequency Fluctuation | 122 | |
| | 4.4.2 | Voltage Fluctuation | 123 | |
| | 4.4.3 | THD _V | 126 | |
| | 4.4.4 | Pst and Plt | 128 | |

| | 4.4.5 An | alysis and Judgement Summary Tables | 129 |
|------|------------|-------------------------------------|-----|
| СНА | PTER 5 | CONCLUSION AND RECOMMENDATIONS | 131 |
| 5.1 | Conclusion | n | 131 |
| 5.2 | Recommen | ndation and Future Works. | 133 |
| REFI | ERENCES | | 134 |
| APPI | ENDICES | | 141 |



LIST OF TABLES

| TABLE | TITLE | PAGE |
|------------|---|------|
| Table 1.1 | MGC Voltage Flickers Specification | 10 |
| Table 1.2 | Summary Table for Power Quality Parameters Specification Under Investigation. | 11 |
| Table 2.1 | Harmonic Specification According To ESAH | 17 |
| Table 2.2 | THD Voltage and Current Measured at PCC by R. Sinvula | 18 |
| Table 2.3 | Current Harmonic Spectrum At PCC by M. Farhoodnea et al | 21 |
| Table 2.4 | Maximum Allowed Capacity For NEM Customer | 23 |
| Table 2.5 | Parameters for Synchronisation for NEM Licensee | 23 |
| Table 2.6 | Minimum Re-Synchronisation Waiting Time for NEM Licensee | 23 |
| Table 2.7 | Individual Harmonics Limit for NEM Customer | 24 |
| Table 2.8 | LV Operating Voltage At PCC For NEM Customer | 26 |
| Table 2.9 | MV Operating Voltage At PCC For NEM Customer | 26 |
| Table 2.10 | Bus System Model Simulation Result by R. Khan et al | 29 |
| Table 2.11 | NEM Guideline voltage flickers specification | 32 |
| Table 2.12 | Comparison Table Between Literature. | 37 |
| Table 2.13 | Summary of Research Gaps | 44 |
| Table 3.1 | Capability Indice Definition and Calculation Formula | 69 |
| Table 3.2 | Pearson Correlation Coefficient Interpretation Guideline | 72 |
| Table 3.3 | Data Offered by Solcat API Toolkit | 75 |
| Table 4.1 | Selected Location and Measurement Schedule | 78 |
| Table 4.2 | Specification of Jinko Solar PV Array | 82 |
| Table 4.3 | Specification of Huawei Sun-2000-100KTL Smart Inverter | 82 |
| Table 4.4 | Protections and Grid Compatability for Huawei Sun-2000-100KTL Smart Inventer | 83 |

| Table 4.5 | Summary of Standards Requirement and Smart Inverter Compliance | 84 |
|------------|--|-----|
| Table 4.6 | Statistical Descriptive Analysis of TMSB 1. | 98 |
| Table 4.7 | Statistical Descriptive Analysis of TMSB 2. | 100 |
| Table 4.8 | Statistical Descriptive Analysis of TMSB 3. | 101 |
| Table 4.9 | Pearson Correlation Between Parameters at TMSB 1. | 117 |
| Table 4.10 | Pearson Correlation Between Parameters at TMSB 2. | 118 |
| Table 4.11 | Pearson Correlation Between Parameters at TMSB 3. | 120 |
| Table 4.12 | Analysis Result Summary. | 129 |
| Table 4.13 | Decision and Judgement Summary. | 130 |



LIST OF FIGURES

| FIGURE | TITLE | PAGE |
|-------------|---|------|
| Figure 1.1 | Simple Grid Connected Solar PV System Diagram | 2 |
| Figure 1.2 | Malaysia Solar Radiation Map And PV Potential | 2 |
| Figure 1.3 | Cost Trend For Solar PV Installation From 2010 to 2018. | 3 |
| Figure 1.4 | Malaysia's Commitment Toward 0% GHG Emmission And Sustainability | 4 |
| Figure 1.5 | Malaysia RE Policy, Objective, Strategies And Action Plan | 4 |
| Figure 1.6 | Graph On Malaysia Solar PV Generation Growth 2011 – 2017 | 5 |
| Figure 1.7 | Simple NEM Connection Diagram | 6 |
| Figure 1.8 | NEM 3.0 Capacity As Of 2022 | 6 |
| Figure 2.1 | Bus 2 And Bus 10 Frequency At Irradiance Of 550 W/m ² | 15 |
| Figure 2.2 | Bus 2 And Bus 10 Frequency At Irradiance Of 650 W/m ² | 15 |
| Figure 2.3 | Bus 2 And Bus 10 Frequency At Irradiance Of 1000 W/m ² | 15 |
| Figure 2.4 | Bus 2 And Bus 10 Frequency At Irradiance Of 850 W/m ² | 15 |
| Figure 2.5 | UNIVERSITI TEKNIKAL MALAYSIA MELAKA Simulation Circuit By M. Zainudin <i>et al</i> | 16 |
| Figure 2.6 | Simulation Circuit by A. Al-Shetwi et al | 16 |
| Figure 2.7 | Frequency Fluctuation at PCC by A. Al-Shetwi et al | 16 |
| Figure 2.8 | Power Factor Dynamic Response at PCC by A. Al-Shetwi et al | 17 |
| Figure 2.9 | Simulation of Multiple Grid Connected Solar PV System | 19 |
| Figure 2.10 | Base Harmonics Measured at PCC by R. Sinvula et al | 19 |
| Figure 2.11 | Voltage Harmonics Measured at PCC by A. Al-Shetwi et al | 20 |
| Figure 2.12 | Current Harmonics Measured at PCC by A. Al-Shetwi et al | 20 |
| Figure 2.13 | 11 Bus System Design and Simulate by M. Farhoodnea et al | 21 |
| Figure 2.14 | Voltage Harmonics After Mitigation By A. Al-Shetwi et al | 22 |

| Figure 2.15 | Current Harmonics After Mitigation by A. Al-Shetwi et al | 22 |
|-------------|--|----|
| Figure 2.16 | MATLAB Solar PV Network Model by S. Kumary et al | 26 |
| Figure 2.17 | Bus Voltage Before PV Penetrations by S. Kumary et al | 27 |
| Figure 2.18 | Bus Voltage After PV Penetrations by S. Kumary et al | 27 |
| Figure 2.19 | Voltage At Solar Irradiance of 550 W/m^2 | 27 |
| Figure 2.20 | Voltage At Solar Irradiance of 650 W/m^2 | 28 |
| Figure 2.21 | Voltage At Solar Irradiance of 850 W/m^2 | 28 |
| Figure 2.22 | Voltage At Solar Irradiance of 1000 W/m ² | 28 |
| Figure 2.23 | 9 Bus System Model by R. Khan et al | 29 |
| Figure 2.24 | Variable Power Injected To 11 Bus System Model by M. Farhoodnea <i>et al</i> | 30 |
| Figure 2.25 | Voltage At Bus 6 by M. Farhoodnea et al | 30 |
| Figure 2.26 | 3 Bus System Model by H. Heidari et al | 31 |
| Figure 2.27 | Voltage at Bus 7 by H. Heidari <i>et al</i> | 31 |
| Figure 2.28 | Voltage Flicker At Bus 6 by M. Farhoodnea et al | 33 |
| Figure 2.29 | Single Source of Solar PV by K. Łowczowski et al | 33 |
| Figure 2.30 | 2 Source of Solar PV by K. Łowczowski <i>et al</i> | 34 |
| Figure 2.31 | 3 Source of Solar PV Penetration by K. Łowczowski et al | 34 |
| Figure 2.32 | Solar PV With DVR by A. Al-Shetwi et al | 35 |
| Figure 2.33 | Solar PV With DVR Equivalent Circuit by A. Al-Shetwi et al | 35 |
| Figure 2.34 | Circuit of Solar PV with STATCOM by M. Malik et al | 36 |
| Figure 2.35 | Injection of Reactive Power by H. Heidari et al | 36 |
| Figure 3.1 | Power Quality Analysis Model by C. J. Melhon | 47 |
| Figure 3.2 | Process Flow Chart For Power Quality Measurement. | 49 |
| Figure 3.3 | Process Flow Chart for Power Quality Analysis. | 50 |
| Figure 3.4 | Process Flow Chart for Frequency Fluctuation Measurement and Analysis | 52 |

| Figure 3.5 | Process Flow Chart for THD _V Measurement and Analysis | 54 |
|-------------|---|----|
| Figure 3.6 | Process Flow Chart for Voltage Fluctuation Measurement and Analysis | 56 |
| Figure 3.7 | Process Flow Chart for Voltage Flickers Measurement and Analysis. | 58 |
| Figure 3.8 | Block Diagram for PQA | 59 |
| Figure 3.9 | Fluke 435 PQA | 59 |
| Figure 3.10 | Specification of Fluke 435 PQA | 60 |
| Figure 3.11 | Measurement Modes Available In Fluke 435 PQA | 60 |
| Figure 3.12 | Block Diagram of PQA Interfacing and Analytical Application | 61 |
| Figure 3.13 | Main Screen of Power Log 5.9 | 61 |
| Figure 3.14 | Data Spreadsheet Of PowerLog 5.9 | 62 |
| Figure 3.15 | Captured Data In Waveform Menu Example [| 62 |
| Figure 3.16 | Harmonics Waveform In Time Progression Mode Example | 63 |
| Figure 3.17 | Harmonics Waveform In Histogram Mode Example | 63 |
| Figure 3.18 | Frequency Unbalance Waveform example | 64 |
| Figure 3.19 | Voltage Flickers Waveform Example | 64 |
| Figure 3.20 | Minitab Software Websites | 65 |
| Figure 3.21 | Opening Data File in Minitab Software. | 66 |
| Figure 3.22 | Selecting Data File in Minitab Software. | 66 |
| Figure 3.23 | Importing Data File in Minitab Software. | 67 |
| Figure 3.24 | Selecting Descriptive Analysis in Minitab Software. | 67 |
| Figure 3.25 | Selecting Data and Parameters for Descriptive Analysis in Minitab Software. | 68 |
| Figure 3.26 | Results for Descriptive Analysis in Minitab Software. | 68 |
| Figure 3.27 | Selecting Capability Analysis in Minitab Software. | 70 |
| Figure 3.28 | Selecting Data and Parameters for Capability Analysis in Minitab Software | 70 |

| Figure 3.29 | Results for Capabilty Analysis in Minitab Software. | 71 |
|-------------|---|----|
| Figure 3.30 | Pearson Correlation Scatter Plot | 72 |
| Figure 3.31 | Selecting Pearson Correlation Analysis in Minitab Software. | 73 |
| Figure 3.32 | Selecting Data and Parameters for Pearson Correlation Analysis in Minitab Software | 73 |
| Figure 3.33 | Results for Pearson Correlation Analysis in Minitab Software. | 74 |
| Figure 3.34 | Solcast API Toolkit Website | 75 |
| Figure 3.35 | PVSYST Website. | 76 |
| Figure 4.1 | Distribution and Interconnection of Sampling Locations. | 80 |
| Figure 4.2 | Installed Solar PV System Block Diagram. | 81 |
| Figure 4.3 | Daily Solar Radiation (Clear Sky) VS Daily Solar Radiation (Effective) on Daily Power Generation (Effective) for 22.11.2022 until 25.11.2022. | 85 |
| Figure 4.4 | Daily Solar Radiation (Clear Sky) VS Daily Solar Radiation (Effective) on Daily Power Generation (Effective) for 25.11.2022 until 29.11.2022. | 86 |
| Figure 4.5 | Daily Solar Radiation (Clear Sky) VS Daily Solar Radiation (Effective) on Daily Power Generation (Effective) for 29.11.2022 until 2.12.2022. | 86 |
| Figure 4.6 | Frequency Fluctuation Recorded at TMSB 1. | 87 |
| Figure 4.7 | Frequency Fluctuation Recorded at TMSB 2. | 88 |
| Figure 4.8 | Frequency Fluctuation Recorded at TMSB 3. | 88 |
| Figure 4.9 | Voltage Fluctuation Trend Recorded at TMSB 1. | 89 |
| Figure 4.10 | Voltage Fluctuation Trend Recorded at TMSB 2. | 90 |
| Figure 4.11 | Voltage Fluctuation Trend Recorded at TMSB 3. | 90 |
| Figure 4.12 | THD _v Trend Recorded at TMBS 1 | 91 |
| Figure 4.13 | THD _v Trend Recorded at TMSB 2 | 91 |
| Figure 4.14 | THD _v Trend Recorded at TMSB 3 | 92 |
| Figure 4.15 | Short Term Flickers (Pst) Fluctuation Trend Recorded at TMSB 1 | 93 |

| Figure 4.16 | Short Term Flickers (Pst) Fluctuation Trend Recorded at TMSB 2 | 93 |
|-------------|---|-----|
| Figure 4.17 | Short Term Flickers (Pst) Fluctuation Trend Recorded at TMSB 3 | 94 |
| Figure 4.18 | Long Term Flickers (Plt) Fluctuation Trend Recorded TMSB 1. | 95 |
| Figure 4.19 | Long Term Flickers (Plt) Fluctuation Trend Recorded TMSB 2. | 95 |
| Figure 4.20 | Long Term Flickers (Plt) Fluctuation Trend Recorded TMSB 3. | 96 |
| Figure 4.21 | Frequency Fluctuation Process Capability at TMSB 1 | 103 |
| Figure 4.22 | Frequency Fluctuation Process Capability at TMSB 2 | 103 |
| Figure 4.23 | Frequency Fluctuation Process Capability at TMSB 3 | 104 |
| Figure 4.24 | Voltage Fluctuation Process Capability at TMSB 1. | 105 |
| Figure 4.25 | Voltage Fluctuation Process Capability at TMSB 2. | 106 |
| Figure 4.26 | Voltage Fluctuation Process Capability at TMSB 3. | 107 |
| Figure 4.27 | THDv Level Process Capability at TMSB 1 | 108 |
| Figure 4.28 | THD _v Level Process Capability at TMSB 2 | 109 |
| Figure 4.29 | THD _v Level Process Capability at TMSB 3 | 110 |
| Figure 4.30 | Short Term Voltage Flickers (Pst) Process Capability at TMSB 1. | 111 |
| Figure 4.31 | Short Term Voltage Flickers (Pst) Process Capability at TMSB 2. | 112 |
| Figure 4.32 | Short Term Voltage Flickers (Pst) Process Capability at TMSB 3. | 113 |
| Figure 4.33 | Long Term Voltage Flickers (Plt) Process Capability at TMSB 1. | 114 |
| Figure 4.34 | Long Term Voltage Flickers (Plt) Process Capability at TMSB 2. | 115 |
| Figure 4.35 | Long Term Voltage Flickers (Plt) Process Capability at TMSB 3. | 116 |
| Figure 4.36 | Correlation Between Power Injected Onto Grid to Line Voltage | 119 |
| Figure 4.37 | Correlation Between Power Injected Onto Grid to Line THD_V | 119 |
| Figure 4.38 | Correlation Between Power Injected Onto Grid and Line Voltage at TMSB 3 | 121 |
| Figure 4.39 | Correlation Between Power Injected Onto Grid and Line THD at TMSB 3 | 121 |

| Figure 4.40 | Correlation Between Power Injected Onto Grid to Line Plt at TMSB 3 | 122 |
|-------------|--|-----|
| Figure 4.41 | Correlation Between Power Consumption vs Voltage at TMSB 2. | 125 |
| Figure 4.42 | Correlation Between Power Consumption vs Voltage at TMSB 3. | 125 |
| Figure 4.43 | Correlation Between Power Consumption vs THD _v at TMSB 2. | 127 |
| Figure 4.44 | Correlation Between Power Consumption vs THD _v at TMSB 3. | 128 |



LIST OF SYMBOLS

| H1 | - Individual harmonics |
|----------|-------------------------------------|
| f | - Frequency |
| Hz | - Hertz |
| P_{lt} | - Absolute long term flicker |
| P_{st} | - Absolute short term flicker |
| kV | - kilovolt |
| W | - Watt |
| Р | - Number of poles |
| Ν | - Rotor speed |
| Т | - Transformer |
| Ζ | - Impedence |
| S | - Reactive power |
| PF | - Power factor |
| V | - Voltage |
| A | Ampere UTEM |
| | |
| | UNIVERSITI TEKNIKAL MALAYSIA MELAKA |

LIST OF ABBREVIATIONS

| NEM | - Net energy metering |
|-------|--|
| SELCO | - Self-consumption |
| PV | - Photovoltaic |
| LSS | - Large scale solar |
| AC | - Alternating current |
| DC | - Direct current |
| THD | - Total harmonic distortion |
| РСС | - Point of common coupling |
| MSB | - Main switch board |
| SEDA | - Sustainable Energy Development Authority |
| RE | - Renewable energy |
| ST | - Suruhanjaya Tenaga |
| TNB | - Tenaga Nasional Berhad |
| MGC | - Malaysian Grid Code |
| LV | - Low voltage |
| MV | 🗧 - Medium voltage |
| HV | - High voltage |
| FACTs | - Flexible AC transmission system |
| PQ | - Power quality |
| PQA | Power Quality Analyzer |
| GHG | - Green house gasses |
| ESAH | Electricity Supply Application Handbook |
| LFRT | - Low Frequency Ride Through |
| HFRT | - HighFrequency Ride Through |
| LVRT | - Low Voltage Ride Through |
| HVRT | - High Voltage Ride Through |

LIST OF APPENDICES

| APPENDIX | TITLE | PAGE |
|------------|-------------------------|------|
| Appendix A | Full Data Table TMSB 1 | 141 |
| Appendix B | Full Data Table TMSB 2 | 148 |
| Appendix C | Full Data Table TMSB 3 | 153 |
| Appendix D | Full Project Flow Chart | 158 |



CHAPTER 1

INTRODUCTION

1.1 Background

Solar photovoltaic (PV) system is a method in which green energy could be harvest from the sun. Through solar PV system, sunlight will excite PV panel in which the excitation will produce direct current (DC) voltage. A single cell of solar PV has the ability to generate about 1 Watt (W) to 2 W electricity. Hence, an array of solar PV panel needed to generate adequate electricity for generation class. Produced DC voltages from solar PV panel then converted to alternate current (AC) voltages through inverters. As the amount of voltages generated are typically low, step up transformer needed to increase the AC voltages to match it with grid requirement. However, in recent years smart inverters with transformerless technologies utilizing the advancement of power electronics had been very popular and adopted by many.

Solar PV systems comprise of a number of components that are integral to its function. In grid connected operation, PV panels produced electricity will be directed to an inverter, which then convert the DC voltage to AC voltage. Next, the output will be increased further by step up transformer before feeding the voltages to the grid through the point of common coupling (PCC). Solar PV systems are made up of a number of arrays that produce reasonably high amounts of power during day time periods. Figure 1.1 shows the basic architechture of solar PV[17].