INTELLIGENT LINE FOLLOWER ROBOT USING LDR SENSOR MOHD HAFIZ BIN ABDUL MANAN

7 MAY 2008

٠	٠	٠
	1	1

"I/ we have approve that I've read the Final Year Project report with my opinion this
report is fulfill the scope and the quality to be honored with the Bachelor of Electrical
Engineering (Control, Instrumentation and Automation).

Signature	·
Supervisors Name	: MADAM AINAIN NUR BINTI HANAFI
Date	:

INTELLIGENT LINE FOLLOWING ROBOT USING LDR SENSOR

MOHD HAFIZ BIN ABDUL MANAN

This Report Is Submitted In Partial Fulfillment of Requirements for the Bachelor Degree of Electrical Engineering (Control, Instrumentation and Automation)

Fakulti Kejuruteraan Elektrik Universiti Teknikal Malaysia Melaka

MAY 2008

٠	٠
1	4

"I hereby declare that the report is the result of my own, as clearly state	ed in the sources
of references and sources is explained and stated."	

Signature	·
Name	: MOHD HAFIZ BIN ABDUL MANAN
Date	· 7 MAY 2008

I dedicate this to both of my beloved parents, Abdul Manan bin Mohd Yusoff and Norani binti Abdul Hamid, my family, supervisor Madam Ainain Nur Bt Hanafi, friends and all electrical engineering community that determines to make the future of engineering lies in our hands.

ACKNOWLEDGEMENT

Special thanks to my supervisor, Madam Ainain Nur Bt. Hanafi for his support, idea, knowledge and sharing his experience to fulfill the objective of this final year project. With her support I gain knowledge from this project. I have learned a lot of project management skill which include the time and cost effective to realize the project.

Also thanks to my friend for spending their time teaching me about the PIC microcontroller connection, which seems to be very difficult for me to understand before. Million thanks to all of my friends that giving me so much supports to obtain the outcomes of this project.

Lastly, thank you to all of my family that has spending many time and money to give a never-ending support. Without them my life would be nothing.

ABSTRACT

This project is about design and implementation mobile robot kit that purpose to education .This mobile robot is capable to differentiate color lines. Microcontroller is use to control all the robot movement depend on the programming. The concept is the LDR sensors differentiate color lines based on color lines resistance. Two LDR sensors are use as an input that send signal to microcontroller to be processed. The compilation of output is showed by an application to a mobile robot which is moves due to the compilation of signal send by LDR sensors. Signal that come from PIC will control the wheel spin with the help of H-bridge and motor. Finally, this project has completed after a string of hardwork and energy done. The objectives achieved and robot capable to differentiate color lines and moved according to program. As for conclusion, Light Dependant Resistor (LDR) can be used to differentiate different color lines with different sensitivity levels.

ABSTRAK

Projek ini adalah untuk mereka dan membina sebuah mobil robot bergerak untuk tujuan pembelajaran. Robot ini berkemampuan untuk membezakan sesuatu warna dan bergerak mengikut arah yang telah ditetapkan. Micropengawal digunakan untuk mengawal keseluruhan pergerakan mobil robot kit ini. Dalam projek ini PIC merupakan pengawal yang akan mengawal segala pergerakan mobil robot bergantung kepada aturcara yang telah tetetapkan. Terdapat dua penderia LDR berfungsi sebagai input yang menghantar isyarat kepadea mikropengawal untuk diproses. Semua kompilasi output akan ditunjukkan melalui pergerakan mobil robot yang bergerak mengikut kompilasi isyarat yang dihantar oleh penderia. Isyarat-isyarat yang akan keluar daripada pin PIC akan mengawal pergerakan roda dengan bantuan H-bridge dan motor. Akhirnya,selepas segala usaha dan tenaga digunakan untuk menyiapkan projek ini, projek ini berjaya disiapkan. Objektif berjaya dicapai dan robot yang terhasil dapat membezakan pelbagai jenis warna dan bergerak mengikut aturcara yang telah ditulis. Secara kesimpulanya, perintang peka cahaya dapat digunakan untuk membezakan pelbagai jenis warna yang berlainan daya sensitivitinya.

TABLE OF CONTENT

CHAPTER	TIT	LE	PAGE
	TIT	LE	i
		PAGE OF ADMISSION	
ii			
	SUP	ERVISOR COMFIRMATION	iii
	DED	DICATION	iv
	ACK	KNOWLEDGEMENT	v
	ABS	TRACT	vi
	ABS	TRAK	vii
	TAB	LE OF CONTENT	iix
	LIST	Γ OF TABLES	xi
	LIST	Γ OF FIGURES	xii
	LIST	T OF ABBREVIATIONS	xiv
1	INT	RODUCTION	1
	1.1	Introduction of the Project	1
	1.2	Objective	1
	1.3	Scope of Work	2
	1.4	Problem Statement	2
2	I.JT	ERATURE REVIEW	4

3	THE	ORITIO	CAL BACKGROUND	8
	3.1	Micro	controller	8
		3.1.1	PIC16F877	11
	3.2	Light	Dependant Resistance	17
		3.2.1	LDR Manufacture	20
		3.2.2	LDR Characteristics	22
		3.2.3	LDR Applications	23
		3.2.4	LDR Resistivity	23
		3.2.5	LDR Resistance	24
		3.2.6	LDR Light Intensity	26
	3.3	Direct	Current (DC) Motor	27
		3.3.1	Transmission System	29
		3.3.2	DC Motor Control	29
	3.4	H-Bri	dge	30
		3.4.1	L293B Integrated Circuit (IC)	31
4	PRO	IFCT N	METHODOLOGY	33
-	4.1		Follower Robot Design	34
	1.1	4.1.1	Power Power	35
			Sensors	35
			Control Logic	35
		4.1.4	C	36
			Chassis	36

	4.2	Robot	methodology	38
	4.3	LDR	circuit methodology	38
	4.4	PIC c	ircuit methodology	39
	4.5	LDR	sensor circuit	39
	4.6	DC m	otor methodology	40
	4.7	Troub	eleshoot methodology	40
	4.8	Projec	et Gantt chart	41
_	DD O			
5			DEVELOPMENT	42
	5.1		opment of mobile robot	42
		5.1.2	Robot operation	46
	5.2	Robot	construction	46
		5.2.1	PIC16F877 circuit	46
		5.2.2	Motor driver circuit	49
		5.2.3	LDR sensor circuit	51
	5.3	Softw	are development	52
		5.3.1	System beginning	52
		5.3.2	Interface system	52
		5.3.3	Starting program	52
	5.4	Exper	nditure cost	56
	5.5	Exper	iments	57
		5.5.1	Testing LDR sensor circuit	57
		5.5.2	Testing H-Bridge circuit	58
		5.5.3	Testing PIC circuit	61
6		RESU	JLT AND ANALYSIS	64
	6.1	Hardy	vare	64

		0.1.1	Sensors signals to PIC	04
		6.1.2	PIC receives signal from sensors	65
		6.1.3	PIC signal to motor driver circuit	69
		6.1.4	Robot movement	74
		6.1.5	Software	75
		6.1.6	Tracks for robot	79
7		DISC	USSION, SUGGESTION AND	88
,			LYSIS	00
	7.1	Discu	ssion	88
	7.2	Sugge	estion	89
	7.3	Concl	usion	90

LIST OF TABLES

NO	TITLE	PAGE
2.1	Flowchart for simple line follower robot	11
3.1	Differences between microcontroller and microprocessor	10
3.2	PIC16F877 Microcontroller Key Features	11
3.3	PIC16F877A specification	15
5.1	Expenditure cost	56
5.2	Output voltage for different colors	58
5.3	Motor rotation observation	60
5.4	Motor direction	61
5.5	Vo for PIC Vdd and Vss pins	63
6.1	Robot movement	65
6.2	Robot movement	66
6.3	Motor movement in simulation circuit	70
6.4	Robot movement	75
6.5	Robot movement in different track	80

LIST OF FIGURES

NO	TITLE	PAGE
2.1	Flowchart for simple line follower robot	7
3.1	PIC16F877 Microcontroller	13
3.2	PIC16F877 Peripheral Figures	14
3.3	PIC16F877 Pinout	16
3.4	Normal collector current vs. object distance graph	18
3.5	Wavelength vs. relay intensity graph	19
3.6	Light Dependent Resistor (LDR)	19
3.7	Photoresistor symbol	20
3.8	LDR diagram	21
3.9	Resistance vs. Lux graph	22
3.10	Photoresistor Voltage Divider Circuits	26
3.11	Low voltage DC motor	28
3.12	Structure of DC Motor	29
3.13	Two basic states of a H-bridge	30
3.14	Two basic states of a H-bridge	30
3.15	L293B Integrated Circuit (IC)	31
3.16	L293B Pinout	32
3.17	L293B Pinout	32
4.1	Mobile robot system block diagram	34
4.2	Project methodology flowchart	37
4.3	Robot methodology flowchart	38
4.4	LDR sensor circuit methodology flowchart	38
4.5	PIC circuit methodology flowchart	39

4.6	Motor driver H-Bridge circuit methodology flowchart	39
4.7	DC motor methodology flowchart	40
4.8	Troubleshooting process methodology flowchart	40
4.9	Project Gantt chart	41
5.1	Mobile robot sketches	43
5.2	Mobile robot pictures	44
5.3	Mobile robot flowcharts	45
5.4	LED blinking simulation program	47
5.5	PIC circuit with RS232 interface	48
5.6	PIC microcontroller circuit	48
5.7	L293B H-Bridge schematic diagram circuit	49
5.8	Motor driver circuit simulation	50
5.9	Motor driver circuit	50
5.10	LDR sensor circuit	51
5.11	LDR sensor schematic diagram circuit	52
5.12	PIC interface with PC	53
5.13	CCS PIC C Compiler software	54
5.14	Successfully compiled program	54
5.15	Code downloader	55
5.16	H-Bridge motor driver circuit	59
5.17	PIC circuit	62
6.1	Robot forward movement	67
6.2	Robot reverse movement	67
6.3	Robot turn right movement	68
6.4	Robot turn left movement	69
6.5	Motor forward reverse circuit	70
6.6	Robot forward movements	71
6.7	Robot reverse movement	72
6.8	Robot turn right direction	73

6.9	Robot turn left direction	74
6.10	Tracks for project	79
6.11	Track 1	81
6.12	Track 2	83
6.13	Track 3	84
6.15	Track 4	86

LIST OF ABBREVIATION

Projek Sarjana Muda **PSM**

PLC Light Dependant Resistor

Personal Computer PC

CPU Central Processing Unit

Input/Output I/O

DC Direct Current

 \mathbf{AC} Alternate Current

RAM Random Access Memory

Electrically Erasable Programmable Read-Only Memory **EEPROM**

Light Emitting Diode **LED**

IC **Integrated Circuit**

PIC Programmable Integrated Circuit

LDR Light Dependant Resistor

LIST OF APPENDIXES

NO	TITLE	PAGE
A	PIC16F877 Specification	93
В	PIC16F877 Pinout Descriptions	95
C	LDR Technical Specification	98
D	Material Resistivity and Temperature Effect	99
E	L293 Technical Specification	100

INTELLIGENT LINE FOLLOWER ROBOT USING LDR SENSOR

MOHD HAFIZ BIN ABDUL MANAN

7 MAY 2008



CHAPTER I

INTRODUCTION

1.1 Introduction

Building a simple line following robot is a good entry point into the world of autonomous robotics. When developing a mobile robot, we can apply the principles of robotics. This project aim is to a built a robot, controlled by a PIC microcontroller that able to perform the required tasks and instruction. The purpose of this project is to implement Light Dependant Resistor (LDR) on a mobile robot to differentiate color lines.

Line following robot is a combination of hardware and software parts. Hardware parts are sensor circuit, microcontroller circuit, voltage regulator circuit, motor driver circuit, chassis and wheels. Software parts are simulation software and programming software using C language.

Combination of hardware and software parts will produce a mobile robot that able to implement the tasks and programs structured.

1.2 Project Objectives

To achieve the requirements, I lined up several objectives of this project:

- 1. To design and built mobile robot using LDR sensor and analyze the outcome of the project.
- 2. By developing sensors, hardware and software, the project enables us to get a deeper understanding of what is required in the design of a mobile robot.
- 3. Expose students on how Programmable Integrated Controller (PIC) functioning as a logic control in robot design.

1.3 Project Scope

In general this project scopes are:

- Design circuit for:
 - LDR sensor
 - PIC microcontroller
 - Motor Driver
- Write program for microcontroller system.
- Circuit simulation using Proteus.
- Combine hardware and software part to combine a mobile robot.
- Present project result and analysis.

If there any problem or error in the robot operation, researches and experiments will be do again and robot design will be modified to achieve the expected results.

1.4 Problem Statement

Nowadays, line follower mobile robots used for education purpose are to be in the market. The implementation of this mobile robot can solved student's problems in

order to learn and studying how to create and design mobile robot. Students also get expose on how to connect Programmable Integrated Controller (PIC) to electronic components such as sensors, motor circuit, and so on. The application of control system also can be learn with this mobile robot project. This project also embraces relevantness of Light Dependant Sensor (LDR) usage in industrial applications nowadays.

19

CHAPTER II

LITERATURE REVIEW

Title : Simple Line Follower Robot

Author: Murat Dilaver Vural

: Atilim University, Department of Electrical and Electronics Engineering.

This project serves as a short term summer practice project for undergraduate engineering students in Atilim University. The purposes of this project are to allow the students to design and implement a model or a complete electromechanical system involving both mechanical and electrical hardware as well as software component that has a great educational value. This project objective is to develop and implement a robot which can follow a curve drawn on a surface with contrasting color, such as a black curve on a white surface.

The hardware design for this project is divided into several units that first can be tested or implemented separately and then combined together. These units are components needed in any basic design and implementation:

Processing unit

• Mobility unit

Sensory unit

• RS232 communication unit