

raf

T58.6 .S22 2005



0000016852

Supervisory control and data acquisition (SCADA) for
distribution automation system (DAS) / Sabaruddin Akibe.


**SUPERVISORY CONTROL AND DATA
ACQUISITION (SCADA) FOR DISTRIBUTION
AUTOMATION SYSTEM (DAS)**

SABARUDDIN BIN AKIBE

November 2005

I admit that I have read this report and in my point of view this report achieved the scope and quality for the purpose of graduation in Bachelor of Electrical Engineering.

(Industrial Power)

Signature : 

Supervisor Name : DR MUSSE MOHAMUD AHMED

Date : 18/11/2008

**SUPERVISORY CONTROL AND DATA ACQUISITION (SCADA) FOR
DISTRIBUTION AUTOMATION SYSTEM (DAS)**

SABARUDDIN BIN AKIBE

**This Report Is submitted In Partial Fulfillment of Requirements for the Degree of
Bachelor in Electrical Engineering (Power Industry)**

**Fakulti Kejuruteraan Elektrik
Kolej Universiti Teknikal Kebangsaan Malaysia**

November 2005

Specially dedicated to

My beloved father and mother, Akibe Bin Muhamad and Dalima Binti Sappa. Also to my brothers and my sister who have encouraged me, guided me and inspired me throughout my journey of education.

ACKNOWLEDGEMENT

Bismillahirrahmanirahim.....

Assalamualaikum and hello, I wish to all the readers. Alhamdulillah, thanks to the Almighty ALLAH with his permission finally I have finished my Projek Sarjana Muda II (PSMII). First of all, I want to thank to my beloved parents, brothers and sister. Thank you for the supported and understanding.

Millions of thank to my supervisor Dr Musse Mohamud Ahmed for his advice and support throughout this project. From the advised, comment and guidance, this project has been accomplished with in the given time.

It is to my advantage that I have received help and support from friends and the staff in the faculty labs and also from the PPK Technologies. My thanks to En.Mohd Jafriddin Bin Amin, En Mohammad Zam Zam and En Fikri who has been lending a helping hand to me. It is of my greatest thanks and joy that I have met with these people.

Last but not least, I wish to thank to all my colleagues in KUTKM also to my partners Kyairul Azmi Bin Baharin and Nornikman Bin Rahimin who was developed a complete system of Distribution Automation System (DAS).

ABSTRACT

Modern Energy Management System (EMS) has high potential of future innovation and modifications. This project focuses to the distribution side, Distribution Automation System (DAS), controlling and monitoring the distribution system and the connected load. Currently, the Supervisory Control and Data Acquisitions (SCADA) system is mainly used at the generation and transmission side (high voltage side) in TNB. The SCADA system analyzes data from the electrical equipment at the substation. In TNB SCADA, it has no information about the electrical parameters directly from the distribution side. The purpose of this project is to operate, control, monitor, activate, and de-activate the system to operate with the help of Remote Terminal Unit (RTU) and Automatic By-pass Switch (ABS). The data obtained from this two devices will be useless without SCADA to handle and manage it. The final target for this project is to come up with small scale SCADA functions and operations aimed at distribution system environment.

ABSTRAK

Sistem Pengurusan Tenaga Elektrik adalah berpotensi tinggi untuk di majukan di masa hadapan secara kreatif dan inovatif. Projek ini memfokuskan pada bahagian pengagihan, sistem pengagihan automasi yang mengawal dan membuat paparan pada sistem tersebut dan bahagian beban yang bersambung. Sistem SCADA yang digunakan di TNB sekarang cuma di bahagian penjanaan dan peggantaran sahaja iaitu bahagian voltan tinggi. Sistem SCADA TNB cuma menganalisa data daripada radas-radas dan tidak ada informasi secara terus tentang parameter dari pencawang-pencawang di bahagian pengagihan. Tujuan utama projek ini adalah untuk mengawal, memaparkan, mengaktif dan mematikan system dengan bantuan *Remote Terminal Unit (RTU)* dan *Automatic Bypass Switch (ABS)*. Data-data yang diperolehi daripada radas tersebut akan diuruskan oleh sistem SCADA. Sasaran akhir projek ini adalah menghasilkan satu skala kecil tentang SCADA yang mampu beroperasi pada sistem pengagihan.

CONTENTS

CHAPTER	TOPICS	PAGE
	TITLE PAGE	i
	DECLARATION	ii
	DEDICATION	iv
	ACKNOWLEDGEMENT	v
	ABSTRACT	vi
	ABSTRAK	vii
	CONTENTS	viii
	LIST OF TABLES	xi
	LIST OF FIGURES	xii
	LIST OF APPENDICES	xiv
1	INTRODUCTION	1
	1.1 Overview	1
	1.2 Transmission and Distribution	2
	1.3 Objective	3
	1.4 Work Scope	3
	1.5 Project Contribution	4
	1.6 Overview of Supervisory Control And Data Acquisitions System (SCADA).	4
	1.7 Overview of Distribution Automation System.	5

2	LITERATURE REVIEW	6
2.1	Overview	6
2.2	Automation System	7
2.2.1	Reduced (O&M) Cost	7
2.2.2	Deferred Capital Expenditure	7
2.2.3	Improve Customer Satisfaction	8
2.2.4	Better Information for Planning and Engineering	8
2.3	Load Management Distribution System (DMS)	8
2.4	Distribution Automation System (DAS)	9
2.5	SCADA and Distribution Automation	10
2.6	Implementation SCADA	11
2.6.1	Data Acquisition System	12
2.6.2	Control Computer	12
2.6.3	Communication Interface	13
2.6.4	Remote Terminal Unit	14
2.6.5	Sectionalizing Switch	15
2.7	Communication Network	15
2.8	Serial Communication	17
2.8.1	RS-232	18
2.8.2	RS-449, RS-422, RS-423	18
2.8.3	RS-232 Cabling	19
2.9	Microsoft Visual Basic	20
2.9.1	Windows IDE	22
3	DESIGN AND SOFTWARE IMPLEMENTATION	24
3.1	Overview	24
3.2	Typical SCADA System	24
3.3	Design Concept	25
3.4	Data Transfer (character frame)	26
3.5	Express Data Transmit	27
3.6	Flow Chart for the Interface	28

	3.7	Building the SCADA System	30
	3.7.1	Creating the Interface SCADA System	30
4		RESULT AND DISCUSSION	33
	4.1	Overview	33
	4.2	Communication Cable	34
	4.3	SCADA Application Interface	35
	4.3.1	Login interface	35
	4.3.2	Main Frame	38
	4.3.3	Alarm Alert	39
	4.3.4	Data log	40
	4.3.5	Module Program of the system	41
	4.3.6	Database Program	43
	4.4	System Operation	45
5		CONCLUSION AND RECOMMENDATION	48
	5.1	Conclusion	48
	5.2	Further Development	49
		REFERENCES	50
		APPENDIX	51

LIST OF TABLES

NO	TITLE	PAGE
2.0	RS-232 connection	19

LIST OF FIGURES

NO	TITLE	PAGE
1.0	Layout of a generation, transmission and Distribution network	2
1.1	System Overview	4
2.0	Distribution Management Systems	9
2.1	Relationship of distribution, control, And communication system	10
2.2	Utility system with SCADA and Distribution Automation [1]	10
2.3	Man- Machine Interface [1]	13
2.4	Typical Architecture of RTU Interfacing [1]	14
2.5	Overview of the serial communication	17
2.6	DB-9 connector	20
2.7	Sample development interface	21
2.8	Windows IDE Visual Basic	22
3.0	Design Concept	25
3.1	Characteristic wave character	26
3.2	Interface Flow chart	28
3.3	Standard Form	31
3.4	Basic Form and Module	31
3.5	Programming Coding	32
4.0	Connection Link	34
4.1	DB-9 Connector	34
4.2	Login Interface	35
4.3	Properties	36
4.4	Coding	37
4.5	Main Frame	38
4.6	Alarm Alert	39
4.7	Coding	39
4.8	Data log Table	40
4.9	Module Coding	41
4.10	Database coding	43

4.11	Starting System	46
4.12	Normal Condition	46
4.13	Fault Detected	46
4.14	Switch Change	47
4.15	Return to Normal	47

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	About System Interface	51
B	Add new user Interface	52
C	Setting Communication Connector Interface	53
D	Station Overview Interface	54

CHAPTER 1

INTRODUCTION

1.1 Overview

SCADA stands for Supervisory Control and Data Acquisition. The acronym has been around for 30 years. SCADA systems in the past years were primarily industrial monitoring systems with limited data gathering and control capability. However, in the last 10 years technology has evolved so that many systems maintain huge historical data repositories and are the front end for implementing and viewing sophisticated control schemes. This project focuses to the distribution system, Distribution Automation System (DAS), controlling the distribution system and the connected load.

In this project the SCADA system will be implemented at the distribution side. The SCADA system consists of remote terminal units (RTU's), sectionalizing switches (automatic by-pass switch), data acquisition system, and communication interface and control computer. Distribution SCADA involves collecting and analyzing information to take decision, implementing the appropriate decision and then verifying whether the desired results are achieved.

1.2 Transmission and Distribution

A typical layout of a generation, transmission and distribution network of a large system which would be made up of the elements is shown in Figure 1.0.




Figure 1.0 : Layout of a generation, transmission and distribution network.[1].

To explain and realize Figure 1.0 that one or more of the elements may be missing in any particular system. For example, in a certain system, there may be no secondary transmission and in another case when the generation station is nearby, there may be no transmission and distribution system. In some other cases also, the distribution part at the generation side only for 33kV and 11kV below, mostly 11kV exist.

High-voltage transmission is carried out at 500kV at PMU Ayer Tawar Perak, Yong Peng Johor, Paka Terengganu and Kapar Selangor but mostly the transmission line in Malaysia is either 275kV or 132kV. The distribution network in Malaysia is 33kV and below and until low voltage side is reached 415V and 240V for three phase and single phase systems.

This project will focus on distribution part of 415V and 240V for single phase.

1.3 Objectives

Objective of this project is to initiate (monitor and control) the SCADA system for operation at the downstream network. Ensure that the SCADA system can communicate with the RTU and automatic by-pass switch. This project also can acquire the necessary information about the parameters such as voltage and current, accurately, quickly and with relative ease, it can also indicate and instruct the automatic by-pass switch at the faulted line. To improve the power management at the distribution side so that it is more efficient and systematic. This project also can control the substation automatically only from the control station and can minimize the use of human resources. It can save time and cost and improve the quality performance of the distribution lines operating switches.

1.4 Work Scope

The SCADA system will concentrate on monitoring and controlling the distribution side. The SCADA system will be connected to the RTU and the automatic by-pass switch. This project focuses on the 240V or single phase line. The control room can communicate with the RTU and automatic by-pass switch through the communication cable that is a RS232 communication link. The control room can send and receive the data from the two devices.

1.5 Project Contribution.

Currently, the SCADA system in Malaysia is only for monitoring and collecting data from the substation and transmission line. This project will upgrade the current system to more enhanced version and the first version for SCADA at the distribution side. This project is not only meant for monitoring the system, it is also meant for controlling the substation by the Remote Terminal Units (RTU) and automatic by pass switches. The control room also can get the accurate and quick parameters from the two devices such as a voltage and current.

So, only from the control station, the switch can be opened or closed and also can get the data required from the substation and distribution line.

1.6 Overview of Supervisory Control and Data Acquisitions System (SCADA).




Figure 1.1 : System Overview

1.7 Overview of Distribution Automation System.

Distribution automation is basically a system that allows for automatic, computerized control of a utility's distribution facilities with little or no human intervention. Before automation, actions such as opening and closing the switches required physical, on site interaction from linemen, which often taken a considerable amount of time. With a Supervisory Control and Data Acquisitions (SCADA) devices, operators are able to open or close the switches from a remote location, even if they are miles away from the actual device's location. With the implementation of distribution automation, these actions become automatically controlled by a computer-based system. The computerized controlled makes these decisions almost instantly and immediately implements the necessary course of action.

The SCADA devices mounted on the pole throughout the system communicate with master stations at their respective substations via a fiber optic, wireless access points, cables, or some similar form of communications. SCADA sends or receives the information from the RTU through the communication link. Control center operators also can manually send out commands if deemed necessary. SCADA devices are capable of collecting data from the field to keep in track of the power factor, voltage, current, power and the frequency.

The distribution automation is also used to prevent the failure and outage from ever occurring. The information gathered by the SCADA can also be utilized by engineering and planning departments for load forecasting. [2]

CHAPTER 2

LITERATURE REVIEW

2.1 Overview

This chapter explains the research related to the distribution management system, distribution automation system, implementation of SCADA and the ability of the communication network. The principle ideas are established before the design of the communication network and the basic concept of the RTU and switches. This chapter also briefs about the software used to develop the interface of SCADA.

2.2 Automated System

For the sake of electrical power distribution reliability, sectionalizing switches are provided along the way of primary and secondary feeders. By adding the fault indicator to the sectionalizing switches (automatic by-pass switch) along with circuit breaker and protective relays at the distribution substation, the system is comfortable and easy to determine fault sections. If a power failure occurs at the primary line, the switch automatically changes to the secondary line to save time and reduce the losses. The switches are used for supply restoration process and to prevent the black out. The action of these switches is controlled from the control center through the Remote Terminal Units (RTU'S). [3]

Automation at the consumer's location includes the ability to remotely: read meters, program time-of-use (TOU) meters, connect/disconnect services, control consumer load and send TOU signals. The expected benefits from automating consumer locations are:

- a) Reduced Operation & Maintenance (O&M) cost
- b) Deferred capital expenditures
- c) Improve consumer satisfaction
- d) Better information for planning and engineering

2.2.1. Reduced (O&M) Cost

Operation & Maintenance costs are reduced through reduced labor requirements and processing of consumer claims. It's saving in time for each task, the number of times each task is performed and the cost to perform for each task. Saving is initially realized in decreased purchased power costs resulting from regulatory legs and rate design practices. These savings are the result of reduced peak demand due to load management and TOU programs. They should be considered to be highly transitory in nature and are more conservatively represented as deferred capital investment for peaking generation. The present value of a short term decrease in power costs may be considered a benefit of consumer automation.[3]

2.2.2 Deferred Capital Expenditures

Through load management and TOU incentive, customer peak demand is reduced and the need for additional facilities is deferred. The present value of the deferred capacity requirements is used to quantify this benefit.

2.2.3 Improve Costumers Satisfaction

Automation system installed in distribution side will improve the costumer's satisfaction. The fault occurs on the line, its just take a minute to solve the problem by automations system. So the costumers still can get the electricity by another supply.

2.2.4 Better Information for Planning and Engineering

All the events happened will record on the database. So the engineer and the operator can do analysis of the system. For the future planning, most of the systems need to be improved. The data on the database will help to make the future planning.

The operators or the technicians can get ready to take action on the field, easy to do maintenances and identify the fault location.

2.3 Load Management in Distribution Management System (DMS)

This occupies controlling system loads by remote control of individual costumer loads. Control consists of suppressing or biasing automatic control of cyclic loads, as well as load switching. Load Management can also be effected by including customers to suppress load during utility selected daily periods by means of time of day rate incentives. Distributions Automation provides the control and monitor ability required for both the load management scenarios and direct control of customer's loads and the monitoring necessary to verify that programmed levels are achieved. Execution of load management provides several possible benefits to the utility and its customers. The function of DMS are shown in Figure 2.0




Figure 2.0 : Distribution Management Systems

2.4 Distribution Automation System (DAS)

The various parameters such as current, voltage, frequency, switch status and powers are recorded in the field at the substation and at the line feeder using a data acquisition device called Remote Terminal Unit. All this parameters are transmitted directly to the control station through a communication media interface. Graphic user interface (GUI) is used to display all the data to the computers.

For any controlling action, like opening or closing the switch or circuit breaker, it must be through the RTU and the control station by the communication channel to remote the action. For this automatic vacuum by-pass switch it can operate automatically, but the SCADA can take over the action if more efficient action or solution is needed. The connection between the distribution, control, and communication system is shown in Figure 2.1